# COMcheck Software Version 4.1.5.3 Mechanical Compliance Certificate

# **Project Information**

Energy Code: 2015 IECC

Project Title: Spindletop MHMR Silsbee, Tx

Location: Silsbee, Texas

Climate Zone: 2a

Project Type: New Construction

Construction Site: 222 Durdin Dr. Silsbee, TX 77656 Owner/Agent:

Designer/Contractor: M&E Consulting 1304 Bertrand Dr. Lafayette, LA 70506

Page

1 of 24

# Additional Efficiency Package(s)

Credits: 1.0 Required 1.0 Proposed

Dedicated Outdoor Air System, 1.0 credit

# **Mechanical Systems List**

# **Quantity System Type & Description**

1 MSAHU-1 (Single Zone):

Heating: 1 each - Central Furnace, Electric, Capacity = 14 kBtu/h

No minimum efficiency requirement applies

Cooling: 1 each - Split System, Capacity = 12 kBtu/h, Air-Cooled Condenser, No Economizer, Economizer exception: None

Proposed Efficiency = 20.80 SEER, Required Efficiency: 13.00 SEER Fan System: MSAHU-1 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 1 Supply, Constant Volume, 425 CFM, 0.0 motor nameplate hp, 70.0 fan efficiency grade

1 MSCU-1 (Single Zone):

Heating: 1 each - Central Furnace, Electric, Capacity = 14 kBtu/h

No minimum efficiency requirement applies

Cooling: 1 each - Split System, Capacity = 12 kBtu/h, Air-Cooled Condenser, No Economizer, Economizer exception: None

Proposed Efficiency = 20.00 SEER, Required Efficiency: 13.00 SEER Fan System: MSAHU-1 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 1 Supply, Constant Volume, 425 CFM, 0.0 motor nameplate hp, 70.0 fan efficiency grade

1 OACU-1 (Single Zone):

VRF Condensing Unit, Air Cooled Heat Pump Heating Mode: Capacity = 135 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 120 kBtu/h,

No minimum efficiency requirement applies

Fan System: None

1 OAHU-1 (Single Zone):

Fan System: OAHU-1 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 2 Supply, Constant Volume, 1200 CFM, 1.5 motor nameplate hp, 70.0 fan efficiency grade

1 EUH-1 (Single Zone):

Heating: 1 each - Unit Heater, Electric, Capacity = 10 kBtu/h

No minimum efficiency requirement applies

Fan System: None

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy

#### Quantity System Type & Description

1 HR-1 (Single Zone):

VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump

Heating Mode: Capacity = 135 kBtu/h,

No minimum efficiency requirement applies

Cooling Mode: Capacity = 120 kBtu/h,

No minimum efficiency requirement applies

Fan System: None

1 HR-2 (Single Zone):

VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump

Heating Mode: Capacity = 160 kBtu/h,

No minimum efficiency requirement applies

Cooling Mode: Capacity = 144 kBtu/h,

No minimum efficiency requirement applies

Fan System: None

1 HR-1/1 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 8 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/1 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 3 Supply, Constant Volume, 350 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-1/2,6 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 15 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/2,6 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 4 Supply, Constant Volume, 390 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-1/4,5 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/4,5 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 5 Supply, Constant Volume, 280 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-1/7 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 48 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/7 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 6 Supply, Constant Volume, 1412 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-1/8,9 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 12 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/8,9 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 7 Supply, Constant Volume, 371 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-1/10,11 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 8 kBtu/h, No Economizer, Economizer exception: None

No minimum efficiency requirement applies

Fan System: HR-1/10,11 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 8 Supply, Constant Volume, 300 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-2/1,2 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 36 kBtu/h, No Economizer, Economizer exception: None

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22

Page

2 of 24

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy

### **Quantity System Type & Description**

No minimum efficiency requirement applies

Fan System: HR-2/1,2 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 9 Supply, Constant Volume, 1201 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-2/3 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 30 kBtu/h, No Economizer, Economizer exception: None No minimum efficiency requirement applies

Fan System: HR-2/3 -- Compliance (Motor nameplate HP method): Passes

Fans

FAN 10 Supply, Constant Volume, 883 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-2/4 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 12 kBtu/h, No Economizer, Economizer exception: None No minimum efficiency requirement applies

Fan System: HR-2/4 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 11 Supply, Constant Volume, 390 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-2/5-7 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 12 kBtu/h, No Economizer, Economizer exception: None No minimum efficiency requirement applies

Fan System: HR-2/5-7 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 12 Supply, Constant Volume, 371 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 HR-2/8 (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 15 kBtu/h, No Economizer, Economizer exception: None No minimum efficiency requirement applies

Fan System: HR-2/8 -- Compliance (Motor nameplate HP method): Passes

Fans:

FAN 13 Supply, Constant Volume, 494 CFM, 0.1 motor nameplate hp, 70.0 fan efficiency grade

1 WH-1:

Electric Storage Water Heater, Capacity: 30 gallons w/ Circulation Pump Proposed Efficiency: 1.20 SL, %/h (if > 12 kW), Required Efficiency: 1.20 SL, %/h (if > 12 kW)

### **Mechanical Compliance Statement**

Compliance Statement: The proposed mechanical design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed mechanical systems have been designed to meet the 2015 IECC requirements in COMcheck Version 4.1.5.3 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Hogan Guidry, P.E.	Joggan Duidy	02-21-2022
Name - Title	Signature	Date

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22

Page

3 of 24

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy

# COMcheck Software Version 4.1.5.3 Inspection Checklist Energy Code: 2015 IECC

Lifely Code. 2013 IECC

Requirements: 90.0% were addressed directly in the COMcheck software

Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
C103.2 [PR2] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the mechanical systems and equipment and document where exceptions to the standard are claimed. Load calculations per acceptable engineering standards and handbooks.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C103.2 [PR3] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the service water heating systems and equipment and document where exceptions to the standard are claimed. Hot water system sized per manufacturer's sizing guide.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C406 [PR9] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	□Complies □Does Not □Not Observable □Not Applicable	

**Additional Comments/Assumptions:** 

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22 Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Page 4 of 24

Section # & Req.ID	Footing / Foundation Inspection	Complies?	Comments/Assumptions
C403.2.4. 5, C403.2.4. 6 [FO9] <sup>3</sup>	future connection to controls. Freeze	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

**Additional Comments/Assumptions:** 

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22 Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck 5 of 24 Page

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck

Report date: 02/21/22

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.1, C404.6.2 [PL3] <sup>1</sup>	automatically switch off the recirculating hot-water system or heat trace.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck

Report date: 02/21/22

Section #	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
& Req.ID C404.6.3	Pumps that circulate water between a	☐Complies	Requirement will be met.
[PL7] <sup>3</sup>	heater and storage tank have controls	Does Not	Requirement will be met.
	that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls	□Complies □Does Not	Requirement will be met.
	that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	
C404.6.3 [PL7] <sup>3</sup>		□Complies □Does Not	Requirement will be met.
	that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls	□Complies □Does Not	Requirement will be met.
	that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	
C404.6.3 [PL7] <sup>3</sup>		$\square$ Complies $\square$ Does Not	Exception: Requirement does not apply.
	that limit operation from startup to <= 5 minutes after end of heating cycle.		
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section			
# & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to $104^{\circ}F$ .	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

I	1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to $104^{\circ}F$ .	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Water distribution system that pumps water from a heated-water supply pipe back to the heated-water source through a cold-water supply pipe is a demand recirculation water system. Pumps within this system have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

**Additional Comments/Assumptions:** 

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22 Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck Page 13 of 24

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C402.2.6 [ME41] <sup>3</sup>	Thermally ineffective panel surfaces of sensible heating panels have insulation >= R-3.5.	□Complies □Does Not □Not Observable	Requirement will be met.
		□Not Applicable	
C403.2.12 .1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.2.12 .1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
.1	HVAC fan systems at design conditions do not exceed allowable	□Complies □Does Not	Requirement will be met.
[ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhp.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.
C403.2.12 .1	HVAC fan systems at design conditions do not exceed allowable	□Complies □Does Not	Requirement will be met.
[ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhp.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.
.3	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
.3	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
.3	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
.3	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15%	□Complies □Does Not	Requirement will be met.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.2.13 [ME71] <sup>2</sup>	Unenclosed spaces that are heated use only radiant heat.	□Complies □Does Not □Not Observable	Requirement will be met.
C403.2.3 [ME55] <sup>2</sup>	HVAC equipment efficiency verified.	□Not Applicable □Complies □Does Not □Not Observable	See the Mechanical Systems list for values.
C402.2.5	Demand south 1 (21.1)	□Not Applicable	Domino and will be asset
	Demand control ventilation provided for spaces >500 ft2 and >25 people/1000 ft2 occupant density and served by systems with air side economizer, auto modulating outside air damper control, or design airflow >3,000 cfm.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section #	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions			
& Req.ID C403.2.6.	Enclosed parking garage ventilation has automatic contaminant detection	☐Complies ☐Does Not	Requirement will be met.			
[ME115] <sup>3</sup>	and capacity to stage or modulate fans to 50% or less of design capacity.	□Not Observable				
C403.2.7 [ME57] <sup>1</sup>		□Not Applicable □Complies	Requirement will be met.			
[[11][57]	systems meeting Table C403.2.7(1) and C403.2.7(2).	□Does Not □Not Observable □Not Applicable				
C403.2.8 [ME116] <sup>3</sup>	Kitchen exhaust systems comply with replacement air and conditioned	Complies Does Not	Requirement will be met.			
	supply air limitations, and satisfy hood rating requirements and maximum exhaust rate criteria.	□Not Observable □Not Applicable				
C403.2.9 [ME60] <sup>2</sup>	HVAC ducts and plenums insulated. Where ducts or plenums are installed	□Complies □Does Not	Requirement will be met.			
	in or under a slab, verification may need to occur during Foundation Inspection.	□Not Observable □Not Applicable				
C403.2.9 [ME10] <sup>2</sup>	Ducts and plenums sealed based on static pressure and location.	□Complies □Does Not	Requirement will be met.			
		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
[IAICTT].		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
[[[[]]]]		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
		□Not Observable □Not Applicable				
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
	Dushusali apartir - 2	□ Not Observable □ Not Applicable	Description and will be most			
C403.2.9. 1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.			
	Ductwork operating > 2 in water	□Not Observable □Not Applicable □Complies	Requirement will be met.			
1.3 [ME11] <sup>3</sup>	Ductwork operating >3 in. water column requires air leakage testing.	Does Not Not Observable	nequirement will be met.			
		□Not Observable □Not Applicable				
1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)						

# & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.2.9.	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[METT].		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	$\square$ Complies $\square$ Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	$\square$ Complies $\square$ Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	$\square$ Complies $\square$ Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
1.3	Ductwork operating >3 in. water column requires air leakage testing.	□Complies □Does Not	Requirement will be met.
[ME11] <sup>3</sup>		□Not Observable □Not Applicable	
6	Multiple zone VAV systems with DDC of individual zone boxes have static	□Complies □Does Not	Requirement will be met.
[ME110] <sup>3</sup>	pressure setpoint reset controls.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6	Multiple zone VAV systems with DDC of individual zone boxes have static	□Complies □Does Not	Requirement will be met.
[ME110] <sup>3</sup>	pressure setpoint reset controls.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6	Multiple zone VAV systems with DDC of individual zone boxes have static	□Complies □Does Not	Requirement will be met.
[ME110] <sup>3</sup>	pressure setpoint reset controls.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Page 16 of 24

Project Title: Spindletop MHMR Silsbee, Tx

Section #	Mochanical Bough In Inchestic	Commissa	Commonts/Assumptions
# & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.4.4.	Multiple zone VAV systems with DDC of individual zone boxes have static	□Complies □Does Not	Requirement will be met.
[ME110] <sup>3</sup>	pressure setpoint reset controls.	□Not Observable □Not Applicable	See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Report date: 02/21/22

Page 17 of 24

Project Title: Spindletop MHMR Silsbee, Tx

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C403.4.4. 6 [ME110] <sup>3</sup>	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.  See the Mechanical Systems list for values.
C408.2.2. 1 [ME53] <sup>3</sup>	Air outlets and zone terminal devices have means for air balancing.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.5, C403.5.1, C403.5.2 [ME123] <sup>3</sup>	Refrigerated display cases, walk-in coolers or walk-in freezers served by remote compressors and remote condensers not located in a condensing unit, have fan-powered condensers that comply with Sections C403.5.1 and refrigeration compressor systems that comply with C403.5.2	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

**Additional Comments/Assumptions:** 

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Page 18 of 24

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C303.3, C408.2.5. 3 [FI8] <sup>3</sup>	Furnished O&M manuals for HVAC systems within 90 days of system acceptance.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.2 [FI27] <sup>3</sup>	HVAC systems and equipment capacity does not exceed calculated loads.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control.  Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.2.4.	Heat pump controls prevent supplemental electric resistance heat	□Complies □Does Not	Requirement will be met.
[FI42] <sup>3</sup>	from coming on when not needed.	□Not Observable □Not Applicable	
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	□Complies □Does Not □Not Observable	Requirement will be met.
C403.2.4.	Thermostatic controls have a 5 °F	□Not Applicable □Complies	Requirement will be met.
1.2 [FI38] <sup>3</sup>	deadband.	□ Does Not □ Not Observable □ Not Applicable	nequirement will be met.
C403.2.4. 1.3 [FI20] <sup>3</sup>	Temperature controls have setpoint overlap restrictions.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2 [FI39] <sup>3</sup>	Each zone equipped with setback controls using automatic time clock or programmable control system.	□Complies □Does Not □Not Observable	Requirement will be met.
C403.2.4. 2.1, C403.2.4. 2.2 [FI40] <sup>3</sup>	Automatic Controls: Setback to 55°F (heat) and 85°F (cool); 7-day clock, 2-hour occupant override, 10-hour backup	□Not Applicable □Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[[141]]		□Not Observable □Not Applicable	
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[[141]]		□Not Observable □Not Applicable	
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C403.2.4. 2.3 [FI41] <sup>3</sup>	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
C403.2.4. 2.3	Systems include optimum start controls.	□Complies □Does Not	Requirement will be met.
[FI41] <sup>3</sup>		□Not Observable □Not Applicable	
C404.3 [FI11] <sup>3</sup>	discharge piping of non-circulating	□Complies □Does Not	Exception: Requirement does not apply.
	systems.	□Not Observable □Not Applicable	
C404.4 [FI25] <sup>2</sup>	All piping insulated in accordance with section details and Table C403.2.10.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
C404.6.1 [FI12] <sup>3</sup>	Controls are installed that limit the operation of a recirculation pump	□Complies □Does Not	Requirement will be met.
	installed to maintain temperature of a storage tank. System return pipe is a dedicated return pipe or a cold water supply pipe.	□Not Observable □Not Applicable	

I	1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck

Report date: 02/21/22

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C406.6 [FI52] <sup>1</sup>	Dedicate outdoor air system efficiency package: Buildings with hydronic and/or multiple-zone HVAC systems are equipped with an independent ventilation system designed to provide >= 100-percent outdoor air to each individual occupied space, as specified by the IMC. The ventilation system is capable of total energy recovery and includes HVAC system controls that manage temperature resets >= 25 percent of delta design supply-air / room-air temp.	□Does Not □Not Observable □Not Applicable	
C408.2.1 [FI28] <sup>1</sup>	Commissioning plan developed by registered design professional or approved agency.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
C408.2.3. 1 [FI31] <sup>1</sup>	HVAC equipment has been tested to ensure proper operation.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
C408.2.3. 2 [FI10] <sup>1</sup>	HVAC control systems have been tested to ensure proper operation, calibration and adjustment of controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.4 [FI29] <sup>1</sup>	Preliminary commissioning report completed and certified by registered design professional or approved agency.	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
C408.2.5. 1 [FI7] <sup>3</sup>	Furnished HVAC as-built drawings submitted within 90 days of system acceptance.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.5. 3 [FI43] <sup>1</sup>	An air and/or hydronic system balancing report is provided for HVAC systems.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.5. 4 [FI30] <sup>1</sup>	Final commissioning report due to building owner within 90 days of receipt of certificate of occupancy.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

**Additional Comments/Assumptions:** 

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22
Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Page 23 of 24

Project Title: Spindletop MHMR Silsbee, Tx Report date: 02/21/22 Data filename: H:\21\21167.00 (Spindletop MHMR Silsbee TX)\Design\Energy Compliance\21167.00 Energy Compliance.cck Page 24 of 24