


SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

1575 HWY 96 N

SILSBEE, TX 77656



OWNER
Silsbee Independent School District
415 TX-327
Silsbee, TX 77656
Contact: Dr. Gregg Weiss
Phone: (409) 385-5286
Email: gregg.weiss@silsbeesd.com

ARCHITECT
ARCHITECTURAL ALLIANCE, INCORPORATED
350 Pine Street Suite 720
Beaumont, Texas 77701
Contact: Rob Clark
Phone: (409) 866-7196
Email: rclark@architect-aa.com

CIVIL
FITZ & SHIPMAN
1405 Cornerstone Court
Beaumont, Texas 77706
Contact: Ben Tristin
Phone: (409) 832-7238
Email: btristin@fitzshipman.com

STRUCTURAL
FITZ & SHIPMAN
1405 Cornerstone Court
Beaumont, Texas 77706
Contact: Daniel Dotson
Phone: (409) 832-7238
Email: ddotson@fitzshipman.com

MECHANICAL, ELECTRICAL, PLUMBING
M&E CONSULTING
1304 Bertrand Drive, Suite F7
Lafayette, Louisiana 70706
Contact: Hogan Guidry
Phone: (337) 234-7474 x103
Email: hogan@meconsulting.com

ABBREVIATIONS

A.B.	ANCHOR BOLT	DR	DOOR	HW	HOT WATER	OPNG	OPENING	THK	THICK(NESS)
A/C	AIR CONDITIONING	DS	DOWNSPOUT	IN	INSIDE DIAMETER	OPP	OPPOSITE	TI	TENANT IMPROVEMENT
ACT	ACOUSTICAL CEILING TILE	DWR	DRAWER	ID	INSIDE DIAMETER	PERP	PERPENDICULAR	TO	TOP OF (SPECIFY ITEM)
A.D.	AREA DRAIN	EA	EACH	IN	INCH	PL	PLATE (OR PROPERTY LINE)	TOC	TOP OF CURB / CONCRETE
ADA	AMERICANS WITH DISABILITIES ACT	EF	EACH FACE / EXHAUST FAN	INCL	INCLUDE(D)	PLAM	PLASTIC LAMINATE	TOP	TOP OF PARAPET
ADJ	ADJUSTABLE	EJ	EXPANSION JOINT	INSUL	INSULATION	PLAS	PLASTER	TOS	TOP OF STEEL
AFF	ABOVE FINISH FLOOR	EIFS	EXTERIOR INSULATED FINISH SYSTEM	INT	INTERIOR	PLYWD	PLYWOOD	TPTN	TOP OF WALL
ALT	ALTERNATE	ELEC	ELECTRICAL	INV	INVERT	PNL	PANEL	TS	TUBULAR STEEL
ALUM	ALUMINUM	ELEV	ELEVATION	JAN	JANITOR	PNT	PAINT	TV	TELEVISION
ANOD	ANODIZED	EMER	EMERGENCY ENCLOSURE	JST	JOIST	PR	PAIR	TYP	TYPICAL
APPROX	APPROXIMATE	ENCL	ENCLOSURE	JT	JOINT	PSF	POUNDS PER SQUARE FOOT	UC	UNDERCOUNTER
ARCH	ARCHITECT(URAL)	EQ	EQUAL EQUIPMENT	KD	KNOCK DOWN	PSI	POUNDS PER SQUARE INCH	UL	UNDERWRITERS LABORATORY
ASPH	ASPHALT	EQIP	EQUIPMENT	KIT	KITCHEN	PT	PRESSURE TREATED PARTITION	UNO	UNLESS NOTED OTHERWISE
BD	BOARD	EW	EACH WAY	KO	KNOCK OUT	PTN	PARTITION	VCT	VINYL COMPOSITION TILE
BIT	BITUMINOUS	EWC	ELECTRIC WATER COOLER	LAB	LABORATORY	PVC	POLYVINYL CHLORIDE	VENT	VENTILATION
BLDG	BUILDING	EXH	EXHAUST	LAM	LAMINATE(D)	RA	RETURN AIR	VERT	VERTICAL
BLKG	BLOCKING	EXIST	EXISTING	LAV	LAVATORY	RAD	RADIUS	VEST	VESTIBULE
BM	BEAM	EXP	EXPANSION / EXPOSED	LF	LINEAL FOOT	RCP	REFLECTED CEILING PLAN	VIF	VERIFY IN FIELD
B.O.	BOTTOM OF	EXT	EXTERIOR	LH	LEFT HAND	RD	ROOF DRAIN	VR	VAPOR RETARDER
BOT	BOTTOM	FD	FLOOR DRAIN	LHR	LEFT HAND REVERSE	REBAR	REINFORCING BAR	VTR	VENT THRU ROOF
BRG	BEARING	FDN	FOUNDATION	LL	LIVE LOAD	REC	RECESSED	VWC	VINYL WALL COVERING
BTWN	BETWEEN	FE	FIRE EXTINGUISHER	LLH	LONG LEG HORIZONTAL	REF	REFERENCE	WC	WATER CLOSET
BUR	BUILT-UP ROOF	FEC	FIRE EXTINGUISHER CABINET	LLV	LONG LEG VERTICAL	REFR	REFRIGERATOR	WD	WOOD
CAB	CABINET	FF	FINISH FLOOR	LWC	LIGHT WEIGHT CONCRETE	REINF	REINFORCING / REINFORCED	WDW	WINDOW
CBU	CEMENTITIOUS BACKER UNIT	FFE	FINISH FLOOR ELEVATION	MACH	MACHINE	REQD	REQUIRED	W/	WITH
C/C	CENTER-TO-CENTER	FIN	FINISH	MAS	MASONRY	RES	RESILIENT	WH	WATER HEATER
CEM	CEMENT	FLR	FLOOR	MATL	MATERIAL	REV	REVISION	W/O	WITHOUT
CER	CERAMIC	FLUOR	FLUORESCENT	MAX	MAXIMUM	RH	RIGHT HAND	WP	WATERPROOF
C.G.	CORNER GUARD	FM	FACTORY MUTUAL	MDF	MEDIUM DENSITY FIBERBOARD	RHR	RIGHT HAND REVERSE	WR	WATER RESISTANT
C.I.P.	CAST-IN-PLACE	FO	FACE OF (SPECIFY ITEM)	MECH	MECHANICAL	RM	ROOM	WT	WEIGHT
C.J.	CONTROL JOINT	FOB	FACE OF BRICK	MEMB	MEMBRANE	RO	ROUGH OPENING	WWF	WELDED WIRE FABRIC
CL	CENTERLINE	FOC	FACE OF CONCRETE	MFR	MANUFACTURER	RWL	RAINWATER LEADER	WWW	WELDED WIRE MESH
CLG	CEILING	FOS	FACE OF STUD	MEZZ	MEZZANINE	R&S	ROD AND SHELF	YD	YARD
CLR	CLEAR(ANCE)	FR	FIRE RESISTIVE	MH	MANHOLE	SC	SOLID CORE		
CLOS	CLOSET	FT	FEET / FOOT	MIN	MINIMUM	SCHED	SCHEDULE		
CMU	CONCRETE MASONRY UNIT	FTG	FOOTING	MIR	MIRROR	SF	SQUARE FEET		
C.O.	CLEAN OUT	FURR	FURRING / FURRED	MISC	MISCELLANEOUS	SHT	SHEET		
COL	COLUMN	GA	GAUGE	MO	MASONRY OPENING	SIM	SIMILAR		
CONC	CONCRETE	GALV	GALVANIZED	MR	MOISTURE RESISTANT	SPEC	SPECIFICATION		
CONSTR	CONSTRUCTION	GB	GRAB BAR	MTL	METAL	SQ	SQUARE		
CONT	CONTINUOUS	GC	GENERAL CONTRACTOR	MULL	MULLION	SS	STAINLESS STEEL		
COORD	COORDINATE	GL	GLASS / GLAZING	N/A	NOT APPLICABLE	ST	STONE		
CORR	CORRIDOR	GND	GROUND	NIC	NOT IN CONTRACT	STC	SOUND TRANSMISSION CLASS		
CTR	CENTER	GR	GRADE	NO.	NUMBER	STD	STANDARD		
C.Y.	CUBIC YARD	GWB	GYPSUM WALLBOARD	NTS	NOMINAL	STL	STEEL		
		GYP	GYPSUM	NTS	NOT TO SCALE	STOR	STORAGE		
DBL	DOUBLE			OC	ON CENTER	STRUCT	STRUCTURAL		
DEMO	DEMOLITION	HB	HOSE BIB	OD	OUTSIDE DIAMETER	SUSP	SUSPENDED		
DEPT	DEPARTMENT	HC	HOLLOW CORE	OFDI	OWNER FURNISHED/ CONTRACTOR INSTALLED	SYM	SYMMETRICAL		
DET	DETAIL	HDR	HEADER	OFI	OWNER FURNISHED/ CONTRACTOR INSTALLED	TAS	TEXAS ACCESSIBILITY STANDARDS		
DIA	DIAMETER	HDWR	HARDWARE	OFI	OWNER FURNISHED/ CONTRACTOR INSTALLED	T&B	TOP AND BOTTOM		
DIAG	DIAGONAL	HM	HOLLOW METAL	OFI	OWNER FURNISHED/ CONTRACTOR INSTALLED	T&G	TONGUE AND GROOVE		
DIM	DIMENSION	HORIZ	HORIZONTAL	OH	OWNER INSTALLED	TBD	TO BE DETERMINED		
DISP	DISPENSER	HT	HEIGHT			TEL	TELEPHONE		
DL	DEAD LOAD	HVAC	HEATING, VENTILATION, AND AIR CONDITIONING			TER	TERRAZZO		
DN	DOWN								

Sheet List Table

Sheet Number	Sheet Title
General	
G000	Cover Sheet
G100	Texas Accessibility Sheet
G101	Texas Accessibility Sheet
G102	Texas Accessibility Sheet
Civil	
C1.00	Dimensional & Grading Plan
Architectural	
A001	Site Plan
A101	Floor Plan
A102	Signage Plan
A700	Building Section
Structural	
S1	Foundation Plan
Mechanical	
M000	Mechanical Legend & Notes
M201	Mechanical Plan
M301	Mechanical Schedules & Details
Electrical	
E000	Electrical Legend
E100	Electrical Demolition Plan
E201	Lighting Plan
E301	Power & Special Systems Plan
E401	Mechanical Power Plan
E501	Electrical Panel Schedules
E601	Electrical Details & Riser
Plumbing	
P000	Plumbing Legend & Notes
P201	Plumbing Plan & Details


MATERIAL LEGEND

	CONCRETE		BLOCKING OR SHIM (CONTINUOUS)
	BRICK MASONRY		BLOCKING OR SHIM (INTERMITTENT)
	CONCRETE MASONRY UNITS		RIGID INSULATION
	PLYWOOD		BATT INSULATION
	GYPSUM BOARD		

SYMBOL KEY

	DOOR NUMBER		PARTITION TYPES
	TOILET ACCESSORY		EXTERIOR ELEVATION TAG
	INTERIOR ELEVATION MARK		ROOM NAME & NUMBER
	ENLARGED DETAIL		WINDOW TYPE
	KEYNOTE		NORTH ARROW

LOCATION MAP



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

Silsbee Independent School District

ISSUED FOR SCHEMATIC DESIGN
DATE: 7/27/2021
DESIGN DEVELOPMENT
DATE: 2/2/2022
BIDS & CONSTRUCTION
DATE: 3/17/2022

DRAWINGS SHEET TITLE
COVER SHEET

SET NUMBER

SHEET NUMBER

G000

21051
PROJECT NUMBER

302 FLOOR OR GROUND SURFACES

302.1 GENERAL. Floor and ground surfaces shall be stable, firm, and slip resistant and shall comply with 302.

EXCEPTIONS:
1. Within animal containment areas, floor and ground surfaces shall not be required to be stable, firm, and slip resistant.
2. Areas of sport activity shall not be required to comply with 302.

302.2 CARPET. Carpet or carpet tile shall be securely attached and shall have a firm cushion, pad, or backing or no cushion or pad. Carpet or carpet tile shall have a level loop, textured loop, level cut pile, or level cut/uncut pile texture. Pile height shall be 1/2 inch (13 mm) maximum. Exposed edges of carpet shall be fastened to floor surfaces and shall have trim on the entire length of the exposed edge. Carpet edge trim shall comply with 303.




Figure 302.2 Carpet Pile Height

302.3 OPENINGS. Openings in floor or ground surfaces shall not allow passage of a sphere more than 1/2 inch (13 mm) diameter except as allowed in 407.4.3, 409.4.3, 410.4, 810.5.3 and 810.10. Elongated openings shall be placed so that the long dimension is perpendicular to the dominant direction of travel.




Figure 302.3 Elongated Openings in Floor or Ground Surfaces

303 CHANGE IN LEVELS

303.1 GENERAL. Where changes in level are permitted in floor or ground surfaces, they shall comply with 303.

EXCEPTIONS:
1. Animal containment areas shall not be required to comply with 303.
2. Areas of sport activity shall not be required to comply with 303.

303.2 VERTICAL. Changes in level of 1/4 inch (6.4 mm) high maximum shall be permitted to be vertical.

303.3 BEVELED. Changes in level between 1/4 inch (6.4 mm) high minimum and 1/2 inch (13 mm) high maximum shall be beveled with a slope not steeper than 1:2.

303.4 RAMPS. Changes in level greater than 1/2 inch (13 mm) high shall be ramped, and shall comply with 405 or 406.

304 TURNING SPACE

304.1 GENERAL. Turning space shall comply with 304.

304.2 FLOOR OR GROUND SURFACES. Floor or ground surfaces of a turning space shall comply with 302. Changes in level are not permitted.

EXCEPTION: Slopes not steeper than 1:48 shall be permitted.

304.3 SIZE. Turning space shall comply with 304.3.1 or 304.3.2.

304.3.1 CIRCULAR SPACE. The turning space shall be a space of 60 inches (1525 mm) diameter minimum. The space shall be permitted to include knee and toe clearance complying with 306.

304.3.2 T-SHAPED SPACE. The turning space shall be a T-shaped space within a 60 inch (1525 mm) square minimum with arms and base 36 inches (915 mm) wide minimum. Each arm of the T shall be clear of obstructions 12 inches (305 mm) minimum in each direction and the base shall be clear of obstructions 24 inches (610 mm) minimum. The space shall be permitted to include knee and toe clearance complying with 306 only at the end of either the base or one arm.




Figure 304.3.2 T-Shaped Turning Space

304.4 DOOR SWING. Doors shall be permitted to swing into turning spaces.

305 CLEAR FLOOR SPACE OR GROUND FLOOR SPACE

305.1 GENERAL. Clear floor or ground space shall comply with 305.

305.2 FLOOR OR GROUND SURFACES. Floor or ground surfaces of a clear floor or ground space shall comply with 302. Changes in level are not permitted.

EXCEPTION: Slopes not steeper than 1:48 shall be permitted.

305.3 SIZE. The clear floor or ground space shall be 30 inches (760 mm) minimum by 48 inches (1220 mm) minimum.




Figure 305.3 Clear Floor or Ground Space

305.4 KNEE AND TOE CLEARANCE. Unless otherwise specified, clear floor or ground space shall be permitted to include knee and toe clearance complying with 306.

305.5 POSITION. Unless otherwise specified, clear floor or ground space shall be positioned for either forward or parallel approach to an element.




Figure 305.5 Position of Clear Floor or Ground Space

305.6 approach. One full unobstructed side of the clear floor or ground space shall adjoin an accessible route or adjoin another clear floor or ground space.

305.7 MANEUVERING CLEARANCE. Where a clear floor or ground space is located in an alcove or otherwise confined on all or part of three sides, additional maneuvering clearance shall be provided in accordance with 305.7.1 and 305.7.2.

305.7.1 FORWARD APPROACH. Alcoves shall be 36 inches (915 mm) wide minimum where the depth exceeds 24 inches (610 mm).




Figure 305.7.1 Maneuvering Clearance in an Alcove, Forward Approach

305.7.2 PARALLEL APPROACH. Alcoves shall be 60 inches (1525 mm) wide minimum where the depth exceeds 15 inches (380 mm).





Figure 305.7.2 Maneuvering Clearance in an Alcove, Parallel Approach


306 KNEE AND TOE CLEARANCE



307 PROTRUDING OBJECTS

307.2 PROTRUSION LIMITS. Objects with leading edges more than 27 inches (685 mm) and not more than 80 inches (2030 mm) above the finish floor or ground shall protrude 4 inches (100 mm) maximum horizontally into the circulation path.

EXCEPTION: Handrails shall be permitted to protrude 4 1/2 inches (115 mm) maximum.



307.3 POST-MOUNTED OBJECTS. Free-standing objects mounted on posts or pylons shall overhang circulation paths 12 inches (305 mm) maximum when located 27 inches (685 mm) minimum and 80 inches (2030 mm) maximum above the finish floor or ground. Where a sign or other obstruction is mounted between posts or pylons and the clear distance between the posts or pylons is greater than 12 inches (305 mm), the lowest edge of such sign or obstruction shall be 27 inches (685 mm) maximum or 80 inches (2030 mm) minimum above the finish floor or ground.

EXCEPTION: The sloping portions of handrails serving stairs and ramps shall not be required to comply with 307.3.




Figure 307.3 Post-Mounted Protruding Objects

307.4 VERTICAL CLEARANCE. Vertical clearance shall be 80 inches (2030 mm) high minimum. Guardrails or other barriers shall be provided where the vertical clearance is less than 80 inches (2030 mm) high. The leading edge of such guardrail or barrier shall be located 27 inches (685 mm) maximum above the finish floor or ground.

EXCEPTION: Door closers and door stops shall be permitted to be 78 inches (1980 mm) minimum above the finish floor or ground.

308 REACH RANGE




Figure 308.2.1 Unobstructed Forward Reach

Figure 308.2.2 Obstructed High Forward Reach

308.3 SIDE REACH.

308.3.1 UNOBSTRUCTED. Where a clear floor or ground space allows a parallel approach to an element and the side reach is unobstructed, the high side reach shall be 48 inches (1220 mm) maximum and the low side reach shall be 15 inches (380 mm) minimum above the finish floor or ground.

EXCEPTIONS:
1. An obstruction shall be permitted between the clear floor or ground space and the element where the depth of the obstruction is 10 inches (255 mm) maximum.
2. Operable parts of fuel dispensers shall be permitted to be 54 inches (1370 mm) maximum measured from the surface of the vehicular way where fuel dispensers are installed on existing curbs.




Figure 308.3.1 Unobstructed Side Reach

Figure 308.3.2 Obstructed High Side Reach

308.3.2 OBSTRUCTED HIGH REACH. Where a clear floor or ground space allows a parallel approach to an element and the high side reach is over an obstruction, the height of the obstruction shall be 34 inches (865 mm) maximum and the depth of the obstruction shall be 24 inches (610 mm) maximum. The high side reach shall be 48 inches (1220 mm) maximum for a reach depth of 10 inches (255 mm) maximum. Where the reach depth exceeds 10 inches (255 mm), the high side reach shall be 46 inches (1170 mm) maximum for a reach depth of 24 inches (610 mm) maximum.

EXCEPTIONS:
1. The top of washing machines and clothes dryers shall be permitted to be 36 inches (915 mm) maximum above the finish floor.
2. Operable parts of fuel dispensers shall be permitted to be 54 inches (1370 mm) maximum measured from the surface of the vehicular way where fuel dispensers are installed on existing curbs.

309 OPERABLE PARTS

309.4 OPERATION. Operable parts shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate operable parts shall be 5 pounds (22.2 N) maximum.

EXCEPTION: Gas pump nozzles shall not be required to provide operable parts that have an actuating force of 5 pounds (22.2 N) maximum.

402 ACCESSIBLE ROUTES

402.2 COMPONENTS. Accessible routes shall consist of one or more of the following components: walking surfaces with a running slope not steeper than 1:20, doorways, ramps, curb ramps excluding the flared sides, elevators, and platform lifts. All components of an accessible route shall comply with the applicable requirements of Chapter 4.

403 WALKING SURFACE

403.3 SLOPE. The running slope of walking surfaces shall not be steeper than 1:20. The cross slope of walking surfaces shall not be steeper than 1:48.

403.5 CLEARANCES. Walking surfaces shall provide clearances complying with 403.5.

EXCEPTION: Within employee work areas, clearances on common use circulation paths shall be permitted to be decreased by work area equipment provided that the decrease is essential to the function of the work being performed.

403.5.1 CLEAR WIDTH. Except as provided in 403.5.2 and 403.5.3, the clear width of walking surfaces shall be 36 inches (915 mm) minimum.

EXCEPTION: The clear width shall be permitted to be reduced to 32 inches (815 mm) minimum for a length of 24 inches (610 mm) maximum provided that reduced width segments are separated by segments that are 48 inches (1220 mm) long minimum and 36 inches (915 mm) wide minimum.




Figure 403.5.1 Clear Width of an Accessible Route

403.5.2 CLEAR WIDTH AT TURN. Where the accessible route makes a 180 degree turn around an element which is less than 48 inches (1220 mm) wide, clear width shall be 42 inches (1065 mm) minimum approaching the turn, 48 inches (1220 mm) minimum at the turn and 42 inches (1065 mm) minimum leaving the turn.

EXCEPTION: Where the clear width at the turn is 60 inches (1525 mm) minimum compliance with 403.5.2 shall not be required.




Figure 403.5.2 Clear Width at Turn

Figure 403.5.2 Clear Width at Turn (EXCEPTION)

403.5.3 PASSING SPACES. An accessible route with a clear width less than 60 inches (1525 mm) shall provide passing spaces at intervals of 200 feet (61 m) maximum. Passing spaces shall be either: a space 60 inches (1525 mm) minimum by 60 inches (1525 mm) minimum; or, an intersection of two walking surfaces providing a T-shaped space complying with 304.3.2 where the base and arms of the T-shaped space extend 48 inches (1220 mm) minimum beyond the intersection.

404 DOORS, DOORWAYS, AND GATES

404.2.3 CLEAR WIDTH. Door openings shall provide a clear width of 32 inches (815 mm) minimum. Clear openings of doorways with swinging doors shall be measured between the face of the door and the stop, with the door open 90 degrees. Openings more than 24 inches (610 mm) deep shall provide a clear opening of 36 inches (915 mm) minimum. There shall be no projections into the required clear opening width lower than 34 inches (865 mm) above the finish floor or ground. Projections into the clear opening width between 34 inches (865 mm) and 80 inches (2030 mm) above the finish floor or ground shall not exceed 4 inches (100 mm).

EXCEPTIONS:
1. In alterations, a projection of 5/8 inch (16 mm) maximum into the required clear width shall be permitted for the latch side stop.
2. Door closers and door stops shall be permitted to be 78 inches (1980 mm) minimum above the finish floor or ground.




Figure 404.2.3.1 Front Approach, Pull Side

Figure 404.2.3.2 Front Approach, Push Side




Figure 406.1 Hinge Approach, Pull Side




Figure 406.1 Hinge Approach, Push Side

Figure 406.1 Latch Approach, Pull Side




Figure 406.1 Latch Approach, Push Side

404.2.6 DOORS IN SERIES AND GATES IN SERIES. The distance between two hinged or pivoted doors in series and gates in series shall be 48 inches (1220 mm) minimum plus the width of doors or gates swinging into the space.

404.2.10 DOOR AND GATE SURFACES. Swinging door and gate surfaces within 10 inches (255 mm) of the finish floor or ground measured vertically shall have a smooth surface on the push side extending the full width of the door or gate. Parts creating horizontal or vertical joints in these surfaces shall be within 1/16 inch (1.6 mm) of the same plane as the other. Cavities created by added kick plates shall be capped.

405 RAMPS

405.2 SLOPE. Ramp runs shall have a running slope not steeper than 1:12.

EXCEPTION: In existing sites, buildings, and facilities, ramps shall be permitted to have running slopes steeper than 1:12 complying with Table 405.2 where such slopes are necessary due to space limitations.

1:8 SLOPE = 3" Maximum Rise
1:10 SLOPE = 6" Maximum Rise




Figure 405.7 Ramp Landings

405.9.1 Extended Floor or Ground Surface. The floor or ground surface of the ramp run or landing shall extend 12 inches (305 mm) minimum beyond the inside face of a handrail complying with 505.

405.9.2 Curb or Barrier. A curb or barrier shall be provided that prevents the passage of a 4 inch (100 mm) diameter sphere, where any portion of the sphere is within 4 inches (100 mm) of the finish floor or ground surface.




Figure 405.9.1 Extended Floor or Ground Surface Edge Protection

Figure 405.9.2 Curb or Barrier Edge Protection

406 CURB RAMPS

406.1 GENERAL. Curb ramps on accessible routes shall comply with 406, 405.2 through 405.5, and 405.10.

406.2 COUNTER SLOPE. Counter slopes of adjoining gutters and road surfaces immediately adjacent to the curb ramp shall not be steeper than 1:20. The adjacent surfaces at transitions at curb ramps to walks, gutters, and streets shall be at the same level.




Figure 406.2 Counter Slope of Surfaces Adjacent to Curb Ramps

406.3 SIDES OF CURB RAMPS. Where provided, curb ramp flares shall not be steeper than 1:10.

406.4 LANDINGS. Landings shall be provided at the tops of curb ramps. The landing clear length shall be 36 inches (915 mm) minimum. The landing clear width shall be at least as wide as the curb ramp, excluding flared sides, leading to the landing.

EXCEPTION: In alterations, where there is no landing at the top of curb ramps, curb ramp flares shall be provided and shall not be steeper than 1:12.

406.5 LOCATION. Curb ramps and the flared sides of curb ramps shall be located so that they do not project into vehicular traffic lanes, parking spaces, or parking access aisles. Curb ramps at marked crossings shall be wholly contained within the markings, excluding any flared sides.






Figure 406.6 Curb Ramp Diagram

406.6 DIAGONAL CURB RAMPS. Diagonal or corner type curb ramps with returned curbs or other well-defined edges shall have the edges parallel to the direction of pedestrian flow. The bottom of diagonal curb ramps shall have a clear space 48 inches (1220 mm) minimum outside active traffic lanes of the roadway. Diagonal curb ramps provided at marked crossings shall provide the 48 inches (1220 mm) minimum clear space within the markings. Diagonal curb ramps with flared sides shall have a segment of curb 24 inches (610 mm) long minimum located on each side of the curb ramp and within the marked crossing.



406.7 ISLANDS. Raised islands at crossings shall be cut through level with the street or have curb ramps at both sides. Each curb ramp shall have a level area 48 inches (1220 mm) long minimum by 36 inches (915 mm) wide minimum at the top of the curb ramp in the part of the island intersected by the crossings. Each 48 inch (1220 mm) minimum by 36 inch (915 mm) minimum area shall be oriented so that the 48 inch (1220 mm) minimum length is in the direction of the running slope of the curb ramp it serves. The 48 inch (1220 mm) minimum by 36 inch (915 mm) minimum areas and the accessible route shall be permitted to overlap.



502 PARKING SPACES

502.2 VEHICLE SPACES. Car parking spaces shall be 96 inches (2440 mm) wide minimum and van parking spaces shall be 132 inches (3350 mm) wide minimum, shall be marked to define the width, and shall have an adjacent access aisle complying with 502.3.

EXCEPTION: Van parking spaces shall be permitted to be 96 inches (2440 mm) wide minimum where the access aisle is 96 inches (2440 mm) wide minimum.




Figure 502.2 Vehicle Parking Spaces

Figure 502.2 Vehicle Parking Spaces (Exception)

502.3.4 LOCATION. Access aisles shall not overlap the vehicular way. Access aisles shall be permitted to be placed on either side of the parking space except for angled van parking spaces which shall have access aisles located on the passenger side of the parking spaces.

502.5 VERTICAL CLEARANCE. Parking spaces for vans and access aisles and vehicular routes serving them shall provide a vertical clearance of 98 inches (2490 mm) minimum.

502.6 IDENTIFICATION. Parking space identification signs shall include the International Symbol of Accessibility complying with 703.7.2.1. Signs identifying van parking spaces shall contain the designation "van accessible." Signs shall be 60 inches (1525 mm) minimum above the finish floor or ground surface measured to the bottom of the sign.

503 PASSENGER LOADING ZONES

503.2 VEHICLE PULL-UP SPACE. Passenger loading zones shall provide a vehicular pull-up space 96 inches (2440 mm) wide minimum and 20 feet (6100 mm) long minimum.











Figure 503.2 Vehicle Pull-up Space

STANDARD METAL SIGN WITH HANDICAP SYMBOL, TEXT IN BLUE ON WHITE BACKGROUND, BOLTED TO POST





SIGN TO BE IN COMPLIANCE WITH THE AMERICAN DISABILITIES ACT & THE TEXAS DEPARTMENT OF LICENSING & REGULATION ARCHITECTURAL BARRIERS ACT #9102
SIGNAGE TO BE DONE BY A PROFESSIONAL SIGN MANUFACTURER
SIGN AT VAN PARKING SPACE TO BE MARKED TO INDICATE THAT SPACE IS VAN ACCESSIBLE



ACCESSIBLE PARKING SPACES

- (a) a paved accessible parking space must include:
- (1) the international symbol of access painted conspicuously on the surface in a color that contrasts the pavement.
 - (2) the words "NO PARKING" painted on any access aisle adjacent to the parking space. The words must be painted:
 - (A) in all capital letters;
 - (B) with a letter height of at least one foot, and a stroke width of at least two inches;
 - (C) centered within each access aisle adjacent to the parking space;
 - (3) a sign identifying the consequences of parking illegally in a paved accessible parking space. The sign must:
 - (A) at a minimum state "Violators Subject to Fine and Towing" in a letter height of at least one inch;
 - (B) be mounted on a pole, post, wall or freestanding board;
 - (C) be no more than eight inches below a sign required by Texas Accessibility Standards, 502.6; and
 - (D) be installed so that the bottom edge of the sign is no lower than 4 feet and no higher than 6 feet above ground level.
- (b) a sign that meets the requirements set in Texas Accessibility Standards, 502.6 that includes the required language in subsection (a)(3)(A) satisfies this section.




SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee, TX 77656
Silsbee Independent School District
1975 Hwy 96 N


ISSUED FOR SCHEMATIC DESIGN	<input checked="" type="checkbox"/>
DATE: 7/27/2021	
DESIGN DEVELOPMENT	<input checked="" type="checkbox"/>
DATE: 2/2/2022	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/17/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE
TEXAS ACCESSIBILITY SHEET
SHEET NUMBER
G102
PROJECT NUMBER
21051


SAVED: LEOT
PLOT: LEO TAN
PLOT DATE: 3/19/2022 9:01 AM
SHEET SIZE: ARCH (expand D) 08.00 x 24.00 (inches)



- LENGTHS OF EROSION CONTROL LOGS SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND AS REQUIRED FOR THE PURPOSE INTENDED. MAXIMUM LENGTH OF LOGS SHALL BE 60' FOR 18" DIAMETER OR 30' FOR 12" DIAMETER LOGS.
- UNLESS OTHERWISE DIRECTED, USE BIODEGRADABLE OR PHOTODEGRADABLE CONTAINMENT MESH ONLY WHERE LOG WILL REMAIN IN PLACE AS PART OF A VEGETATIVE SYSTEM. FOR TEMPORARY INSTALLATIONS, USE RECYCLABLE CONTAINMENT MESH.
- STUFF LOGS WITH SUFFICIENT FILTER MATERIAL TO ACHIEVE DENSITY THAT WILL HOLD SHAPE WITHOUT EXCESSIVE DEFORMATION.
- STAKES SHALL BE 2" X 2" WOOD OR #3 REBAR, 4' LONG, EMBEDDED SUCH THAT 2" PROTRUDES ABOVE LOG, OR AS DIRECTED.
- DO NOT PLACE STAKES THROUGH CONTAINMENT MESH.



- GRADING NOTES:**
- CONTRACTOR TO VERIFY ALL ELEVATIONS AND DIMENSIONS BEFORE WORK IS TO BEGIN. VERIFY DIMENSIONS WITH ARCHITECTURAL DRAWINGS AND SECTIONS, NOTIFY ARCHITECT OF ANY CONFLICTS.
 - CONTRACTOR VERIFY ALL EDGE OF PAVEMENTS WHERE PROPOSED PAVEMENTS CONNECTS TO EXISTING EDGE OF PAVEMENTS WHERE ELEVATIONS WERE NOT RECORDED. PROPOSED ELEVATIONS WERE INTERPOLATED BY FROM ELEVATIONS RECORDED.
 - CONTRACTOR TO ENSURE THE ACCESSIBILITY ROUTE ALONG EXISTING AND PROPOSED SIDEWALKS TO COMPLY WITH ACCESSIBILITY STANDARDS.
MAXIMUM CROSS SLOPE OF SIDEWALK - 1:50 OR 2.0%
MAXIMUM LONGITUDINAL SLOPE OF SIDEWALK - 1:200 OR 0.5%
MAXIMUM CHANGES IN VERTICAL ELEVATION - 1/4"
 - FIELD VERIFY THE EXISTING BUILDING DIMENSIONS AND ELEVATIONS, PRIOR TO CONSTRUCTION.
 - CONTRACTOR TO LOCATE ALL AREAS IN WHICH WATER IS COLLECTED AND GRADE AREAS TO PREVENT STANDING WATER.
 - FIELD VERIFY THE EXISTENCE OF UTILITIES ON SITE SHOWN AND NOT SHOWN BEFORE WORK TO BEGIN.
 - EXISTING LANDSCAPE NOT SHOWN, CONTRACTOR TO AVOID DAMAGING OR REMOVING EXISTING LANDSCAPING. EXISTING MAY BE RELOCATED OR OFFSET ELSEWHERE ON SITE.



* UNLESS OTHERWISE NOTED

USAGE	SIZE	*TYPE OF PIPE
FIRE WATERLINE	LESS THAN 4"	Per Building Code
FIRE WATERLINE	4" AND LARGER	C-900 PVC DR-14 200PSI CLASS

NOTE: ALL WATER AND SANITARY SEWER LINES ON SITE ARE PRIVATE.

- GENERAL WATER/SEWER CONSTRUCTION NOTES:**
- ELECTRICAL AND GAS LINES SHALL BE 12" BELOW PUBLIC WATER & SANITARY (TYPICAL).
 - ALL WATER AND SEWER PIPES SHALL HAVE MINIMUM 3 FEET OF COVER
 - THE LOCATION OF ALL EXIST. SERVICE LINES SHOWN ARE APPROXIMATE.


- GENERAL CONSTRUCTION NOTES:**
- PROPOSED SITE UTILITIES, WATER, SANITARY, & ELECT, ARE SHOWN FOR INFORMATIONAL PURPOSE ONLY. REF MEP SHTS FOR MORE INFORMATION.
 - CONTRACTOR TO VERIFY ALL FLOWLINES ON M.E.P. SITEPLAN & GRADING/DRAINAGE PLANS TO AVOID ANY PIPE CONFLICTS
 - CONTRACTOR TO VERIFY FLOWLINES AT ALL TIE-IN POINTS AT THE BUILDING WITH M.E.P. DRAWINGS.
 - THE LOCATION OF ALL EXIST. SERVICE LINES SHOWN ARE APPROXIMATE.
 - CONTRACTOR SHALL OBTAIN ALL STATE & LOCAL PERMITS REQUIRED, INCLUDING BUT NOT LIMITED TO DOT PERMITS.

EXIST. UTILITIES TO REMAIN DO NOT DAMAGE! REPAIRS AT CONTRACTOR'S EXPENSE

CONTRACTOR TO IDENTIFY ALL EXISTING UTILITIES WITHIN CONSTRUCTION SITE SHOWN OR NOT SHOWN ON THIS DRAWING. FLAG AND PROTECT ALL EXISTING UTILITIES THROUGHOUT CONSTRUCTION ACTIVITIES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY ANY AND ALL UTILITIES.



Dimensional Plan & Grading Plan



FILE # 22013.000_CE_SITE PROJECT # 22013.000

Fittz & Shipman
Consulting Engineers and Land Surveyors
T.B.P.E. Firm #1180 T.X.L.S. Firm #100186
1405 Cornerstone Court
Beaumont, TX, 77706
Ph. (409) 832-7238
Fax. (409) 832-7303
www.fittzshipman.com

OWNERSHIP OF DOCUMENTS
THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN INSTRUMENT OF PROFESSIONAL SERVICE, IS THE PROPERTY OF FITTZ & SHIPMAN, INC. AND IS NOT TO BE USED, IN WHOLE OR IN PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF FITTZ & SHIPMAN, INC.
© COPYRIGHT 2022 FITTZ & SHIPMAN, INC.

CALL BEFORE YOU DIG!
TEXAS ONE CALL SYSTEM
1-800-344-8377

CONCRETE PAVEMENT
#3 REBAR @ 12" O.C.E.W.
LIGHT BROOM FINISH
3500 P.S.I. COMPRESSIVE STRENGTH CONCRETE
D = CONCRETE THICKNESS (SEE JOINT LAYOUT FOR PAVEMENT THICKNESS)
PLASTIC REINFORCING CHAIRS @ 48" O.C.E.W.
*MIN. 12" SELECT FILL SUBGRADE TO THEN BE COMPACTED TO 95% STANDARD PROCTOR DENSITY (ASTM 699). SUBGRADE SHALL EXTEND 12" BEYOND EDGE OF PAVEMENT.
PROOF ROLL SUBGRADE AND REMOVE SOFT SPOTS

Architectural Alliance Incorporated
3507 Hwy 98E, Suite 720
Beaumont, Texas 77701
TEL: (409) 896-2496
FAX: (409) 896-4145
J. ROSS CLARK, AIA
RONALD W. LARK, AIA
www.aalliance.com

SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee Independent School District
Silsbee, TX 77656
1975 Hwy 98 E

ISSUED FOR SCHEMATIC DESIGN [X]
DATE: 1-12-2021

DESIGN DEVELOPMENT [X]
DATE: 2/2/2022

BIDS & CONSTRUCTION [X]
DATE: 3/7/2022

REVISION: _____
DATE: _____

REVISION: _____
DATE: _____

REVISION: _____
DATE: _____


DRAWINGS SHEET TITLE
DIMENSIONAL & GRADING PLAN

SHEET NUMBER
C1.00


PROJECT NUMBER
21051

OWNERSHIP OF DRAWINGS THIS DOCUMENT AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN INSTRUMENT OF PROFESSIONAL SERVICES, IS THE PROPERTY OF ARCHITECTURAL ALLIANCE INCORPORATED AND IS NOT TO BE USED, IN WHOLE OR IN PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF ARCHITECTURAL ALLIANCE INCORPORATED. © COPYRIGHT 2022

SAVED: LEOT
 PLOT: LEO TAN
 PLOT DATE: 3/17/2022 12:06 PM
 SHEET SIZE: ARCH (standard D) (36.00 x 24.00 inches)



1 SITE PLAN
 SCALE: 3/32" = 1'-0"



GENERAL CONTRACTOR, BY STATE LAW, TO PROVIDE FOUR ENGRAVED EXIT MICARTA SIGNAGE UNITS TO BE MOUNTED ON THE WALL ADJACENT TO DESIGNATED DOOR, FURNISH AND INSTALL A METAL SIGN WITH 5" HEIGHT STROKE DOOR NUMBER MOUNTED ON THE UPPER CENTER PORTION OF THE DOOR, AND FURNISH AND INSTALL A METAL SIGN WITH 5" HEIGHT STROKE DOOR NUMBER MOUNTED ON THE UPPER CENTER OF THE DOOR. COORDINATE THIS WITH THE ARCHITECT TO ASSURE PROPER COMPLIANCE.



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
 Silsbee, TX 77656
 Silsbee Independent School District
 1575 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input checked="" type="checkbox"/>
DATE: 1-12-2021	
DESIGN DEVELOPMENT	<input checked="" type="checkbox"/>
DATE: 2/2/2022	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/7/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE	SITE PLAN
SHEET NUMBER	A001
PROJECT NUMBER	21051

NEW GIRTS, KYNAR EXTERIOR "R" WALL PANELS, INTERIOR LINER METAL WALL PANELS AND BUILDING INTEGRATED VINYL FACED INSULATION SYSTEM

NEW TEA AND TDLR REQUIRED EXIT SIGNAGE AT DOOR MOUNTED HEIGHT PER TDLR STANDARDS SHEET NOTING "DOOR NO 5" AND PROVIDE AND INSTALL METAL SIGNAGE 5" MINIMUM CHARACTER HEIGHT READING "5" MOUNTED TO UPPER EXTERIOR FACE OF DOOR

NEW PAIR 3'-0" X 7'-0" GALVANIZED DOORS, FRAME, TDLR COMPLIANT PANIC BAR EXIT HARDWARE, THRESHOLD, OVERHEAD CLOSER, WEATHER STRIPPING AND CENTER REMOVABLE MULLION. REFERENCE STRUCTURAL/CIVIL DRAWINGS AND FOR NEW CONNECTING WALK AND SERVICE DRIVE

NEW WALL HUNG FIRE EXTINGUISHER

PROVIDE POWER TO OWNER'S GRINDING STATIONS

NEW 25' WIDE x 15' TALL OVERHEAD MANUALLY OPERATED COILING DOOR ENGINEERED FOR REQUIRED WIND PRESSURE LOADS.

TYPICAL CONCRETE ELEVATED BASE FOR ALL EXISTING PRE-ENGINEERED STEEL BUILDING COLUMNS WHICH REQUIRED CONTRACTOR COORDINATION TO WRAP WALL GIRTS DOWN SIDES TO SECURE NEW EXTERIOR AND INTERIOR WALL PANELS, AND FLASHED/CAULKED TO CONCRETE TO PREVENT WATER INTRUSION TOWARDS THE INTERIOR.

NEW GIRTS, KYNAR EXTERIOR "R" WALL PANELS, INTERIOR LINER METAL WALL PANELS AND BUILDING INTEGRATED VINYL FACED INSULATION SYSTEM

NEW TEA AND TDLR REQUIRED EXIT SIGNAGE AT DOOR MOUNTED HEIGHT PER TDLR STANDARDS SHEET NOTING "DOOR NO 4" AND PROVIDE AND INSTALL METAL SIGNAGE 5" MINIMUM CHARACTER HEIGHT READING "4" MOUNTED TO UPPER EXTERIOR FACE OF DOOR

NOTE: PROVIDE TWO ADDITIONAL INTERIOR TDLR COMPLIANT EXIT SIGNAGE AND TWO ADDITIONAL EXTERIOR DOOR SIGN UNITS READING "2" AND THE SECOND READING "3", COORDINATE SIGNAGE DESIGN REQUIREMENT AND MOUNTING LOCATIONS WITH ARCHITECT PRIOR TO FABRICATION.

NEW 3'-6" X 7'-0" PAINTED GALVANIZED EXIT DOORS AND FRAME WITH TDLR COMPLIANT PANIC BAR EGRESS HARDWARE, WEATHERSTRIPPING, AND THRESHOLD

EXISTING WELDING STATIONS RELOCATED BY G.C. FROM NEW BOY'S DRESSING ROOM

EXISTING WELDING STATIONS TO REMAIN IN-PLACE

REMOVE EXISTING 4' DOOR AND HARDWARE LEAVING FRAME

NEW 7'-4" TALL 8" CMU REINFORCED WALL AND PAINTED GALVANIZED PAINTED STEEL 4' X 6'-8" CASED OPENING FRAMES LEAVING SPACE BETWEEN EXISTING CEILING FOR AIR FLOW. PROVIDE TDLR COMPLIANT SIGN NOTING "DRESSING"

UNDER ALTERNATE NO. 1 PROVIDE PRICE TO REMOVE EXISTING COILING DOOR AND FRAME AND INFILL OPENING WITH NEW STRUCTURAL GIRTS, VINYL FACED INSULATION, AND METAL SIDING EACH SIDE TO MATCH EXISTING

CONTRACTOR TO RELOCATE EXISTING AND NEW OWNER CONSTRUCTED WELDING LOCKER UNITS PLACED AS SHOWN THIS PLAN


CONTRACTOR REMOVE EXISTING LOCKER UNITS DASHED

EXISTING PAINT BOOTH AREA MUST BE SEALED OFF AIR-TIGHT FROM THE WELDING AREA AT INTERSECTION OF NEW ROOF AND WALL PANELS




NOTE: THIS END OF THE EXISTING BUILDING TO REMAIN COMPLETELY OPEN FROM BOTTOM OF ROOF GIRTS TO FINISHED SLAB ELEVATION

NEW WALL HUNG FIRE EXTINGUISHER

1 FLOOR PLAN
SCALE: 3/16" = 1'-0"




SAVED: R08C
PLOT: LEO TAN
PLOT DATE: 3/17/2022 12:06 PM
SHEET SIZE: ARCH (standard D) 24.00 (inches)



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee, TX 77656
Silsbee Independent School District
1975 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input checked="" type="checkbox"/>
DATE: 1-12-2022	
DESIGN DEVELOPMENT	<input checked="" type="checkbox"/>
DATE: 2/2/2022	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/7/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE	FLOOR PLAN
SHEET NUMBER	A101
PROJECT NUMBER	21051




703.4.1 SIGN HEIGHT ABOVE FINISH FLOOR OR GROUND.
TACTILE CHARACTERS ON SIGNS SHALL BE LOCATED 48" MIN. ABOVE FINISH FLOOR FROM THE BASELINE OF LOWEST TACTILE CHARACTER AND 60" MAX. ABOVE FINISH FLOOR FROM THE BASELINE OF HIGHEST TACTILE CHARACTER.





703.4.2 LOCATION
SIGN SHALL BE LOCATED ALONGSIDE THE DOOR AT LATCH SIDE. AT DOUBLE DOORS WITH ONE ACTIVE LEAF, LOCATE SIGN ON INACTIVE LEAF. AT DOUBLE DOORS WITH BOTH ACTIVE LEAVES, LOCATE SIGN AT THE RIGHT OF RIGHT HAND DOOR. WHERE NO WALL SPACE IS AVAILABLE, LOCATE SIGN AT THE NEAREST ADJACENT WALL. SIGNS CONTAINING TACTILE LETTERS SHALL BE LOCATED SO THAT A 18"x18" MIN. CLEAR FLOOR SPACE CENTERED ON TACTILE CHARACTERS, IS PROVIDED BEYOND THE ARC OF ANY DOOR SWING BETWEEN A CLOSED POSITION AND A 45° OPEN POSITION.

SIGNAGE GENERAL NOTES

1. VERIFY ALL SIGNAGE WITH OWNER/ARCHITECT.
2. PROVIDE MICARTA SIGNAGE WITH 3/8" HIGH TEXT AND TDLR / TAS 2012 COMPLIANT BRAILLE. RAISED AND COLOR CONTRAST.
3. ALL ROOM SIGNAGE TO BE MOUNTED 4'-0" MIN TO BOTTOM OF TACTILE CHARACTERS ABOVE FINISH FLOOR TO ADA STANDARD AS DIRECTED BY ARCHITECT.
4. ALL ROOM SIGNAGE TO BE MOUNTED WITH A CLEAR FLOOR SPACE OF 18" x 18" MINIMUM CENTERLINE OF TACTILE CHARACTERS, BEYOND THE ARC OF THE DOOR SWING TO ADA STANDARD AS DIRECTED BY ARCHITECT.
5. ALL TEXT AND BRAILLE RAISED AND COLORS CONTRASTING. TO BE VERIFIED PRIOR TO PREPARATION OF SHOP DRAWINGS.
6. PROVIDE SCALED LAYOUT OF ALL SIGNAGE.
7. HUMAN FIGURE, FONT TYPE, FONT SIZE AND BRAILLE TEXT SHOWN FOR GRAPHIC REPRESENTATION PURPOSES ONLY.



1 SIGNAGE PLAN
SCALE: 3/16" = 1'-0"



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee Independent School District
Silsbee, TX 77656
1975 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input checked="" type="checkbox"/>
DATE: 1-12-2022	
DESIGN DEVELOPMENT	<input checked="" type="checkbox"/>
DATE: 2/2/2022	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/7/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE	SIGNAGE PLAN
SHEET NUMBER	A102
PROJECT NUMBER	21051

SAVED: R06C
PLOT: LEO TAN
PLOT DATE: 3/17/2022 12:07 PM
SHEET SIZE: ARCH (expand D) (36.00 x 24.00 inches)

DEFINE

MECHANICAL ABBREVIATIONS

AD	ACCESS DOOR	HWS	HEATING HOT WATER SUPPLY
ADA	AMERICANS WITH DISABILITIES ACT	HWR	HEATING HOT WATER RETURN
AFF	ABOVE FINISHED FLOOR	KH	KITCHEN HOOD
AHU	AIR HANDLING UNIT	KW	KILOWATT
APD	AIR PRESSURE DROP	LAT	LEAVING AIR TEMPERATURE
BOD	BOTTOM OF DUCT	LWT	LEAVING WATER TEMPERATURE
BOP	BOTTOM OF PIPE	MBH	1000 BRITISH THERMAL UNITS PER HOUR
BTUH	BRITISH THERMAL UNITS PER HOUR	MVD	MANUAL VOLUME DAMPER
C	CONDENSATE	N.O.	NORMALLY OPEN
CFM	CUBIC FEET PER MINUTE	N.C.	NORMALLY CLOSED
CT	CHILLER	NTS	NOT TO SCALE
CHS	CHILLED WATER SUPPLY	NC	NOISE CRITERIA
CHR	CHILLED WATER RETURN	OA	OUTSIDE AIR
COP	COEFFICIENT OF PERFORMANCE	OBD	OPPOSED BLADE DAMPER
CT	COOLING TOWER	PD	PRESSURE DROP
CU	CONDENSING UNIT	PHWR	PLANT HEATING HOT WATER RETURN
CV	CONSTANT VOLUME	PHWS	PLANT HEATING HOT WATER SUPPLY
CS	CONDENSER WATER SUPPLY	PRV	PRESSURE REDUCING VALVE
CR	CONDENSER WATER RETURN	PSIG	POUNDS PER SQUARE INCH GAGE
DB	DRY BULB	RA	RETURN AIR
DOAS	DEDICATED 100% OUTSIDE AIR UNIT	RH	RELATIVE HUMIDITY
EA	EXHAUST AIR	RHC	REHEAT COIL
EAT	ENTERING AIR TEMPERATURE	RPM	REVOLUTIONS PER MINUTE
ECO	EXTERIOR CLEANOUT	RTU	ROOFTOP A/C UNIT
EDH	ELECTRIC DUCT HEATER	SA	SUPPLY AIR
EER	ENERGY EFFICIENCY RATIO	SD	STORM DRAIN
EF	EXHAUST FAN	SEER	SEASONAL ENERGY EFFICIENCY RATIO
EMS	ENERGY MANAGEMENT SYSTEM	SF	SUPPLY FAN
ESP	EXTERNAL STATIC PRESSURE	SP	STATIC PRESSURE
EUH	ELECTRIC UNIT HEATER	SWR	SIDE WALL REGISTER
EWC	ELECTRIC WATER COOLER	TSP	TOTAL STATIC PRESSURE
EWB	ELECTRIC WATER HEATER	TYP	TYPICAL
EWT	ENTERING WATER TEMPERATURE	UNO	UNLESS NOTED OTHERWISE
F	FAHRENHEIT	VAV	VARIABLE AIR VOLUME
FCO	FLOOR CLEANOUT	VFD	VARIABLE FREQUENCY DRIVE
FD	FLOOR DRAIN	VRF	VARIABLE REFRIGERANT FLOW
FLA	FULL LOAD AMPS	WB	WET BULB
FFE	FINISHED FLOOR ELEVATION	WG	WATER GAGE
FPI	FINS PER INCH	WPD	WATER PRESSURE DROP
HP	HORSEPOWER		

DESIGN

MECHANICAL LEGEND


GRILLES, REGISTERS, DIFFUSERS, AND LOUVERS				EQUIPMENT			
EXISTING	DEMO	NEW	DESCRIPTION	EXISTING	DEMO	NEW	DESCRIPTION
		A100	GRILLE DESIGNATION AND CFM				MECHANICAL EQUIPMENT. REFER TO SCHEDULES
			SURFACE MOUNT				IONIZATION UNIT
			LAY-IN SUPPLY CEILING DIFFUSER				SMOKE DETECTOR
			SUPPLY WALL DIFFUSER				MANUAL PULL STATION
			LINEAR SLOT DIFFUSER	CONTROLS			
			RETURN/EXHAUST CEILING GRILLE				THERMOSTAT
			RETURN/EXHAUST WALL GRILLE				HUMIDISTAT
			EXHAUST LOUVER				SENSOR
			EXHAUST WALL CAP				STATIC PRESSURE SENSOR
			GRAVITY RELIEF HOOD				REMOTE TEMPERATURE SENSOR
			INTAKE LOUVER				WALL SWITCH
			INTAKE WALL CAP				CONTROL WIRING
			GRAVITY INTAKE HOOD				
DUCTWORK							
EXISTING	DEMO	NEW	DESCRIPTION				
			RECTANGULAR DUCTWORK. REFER TO PLANS FOR SIZE.				
			ROUND DUCTWORK. REFER TO PLANS FOR SIZE.				
			ROUND DUCTWORK DROP/RISE.				
			DUCT DROP/RISE				
PIPING							
EXISTING	DEMO	NEW	DESCRIPTION				
			CHILLED WATER SUPPLY PIPING				
			CHILLED WATER RETURN PIPING				
			HOT WATER SUPPLY PIPING				
			HOT WATER RETURN PIPING				
			CONDENSER WATER SUPPLY PIPING				
			CONDENSER WATER RETURN PIPING				
DAMPERS							
EXISTING	DEMO	NEW	DESCRIPTION				
			BALANCING DAMPER				
			MOTORIZED DAMPER				
			FIRE DAMPER				
			SMOKE DAMPER				
			FIRE & SMOKE DAMPER				
NOTES: 1. EXISTING ITEMS ON DEMO PLANS ARE "EXISTING TO REMAIN" UNLESS NOTED "EXISTING TO BE RELOCATED." 2. ITEMS ON NEW CONSTRUCTION PLANS ARE NEW UNLESS NOTED "RELOCATED FROM PREVIOUS LOCATION." 3. REFER TO SCHEDULES FOR GRILLE, REGISTER, DIFFUSER, AND LOUVER SIZES. 4. REFER TO DRAWINGS FOR DIRECTION OF AIRFLOW FOR DIFFUSERS. IF DIRECTIONAL ARROWS ARE NOT INCLUDED, AIRFLOW IS IN FOUR DIRECTIONS. (4-WAY GRILLE) 5. WALL MOUNTED CONTROL DEVICES SHALL BE MOUNTED AT 48" A.F.F. 6. NOT ALL ITEMS SHOWN ON THIS LIST MAY BE APPLICABLE TO THIS PROJECT.							

DELIVER

MECHANICAL GENERAL NOTES

- CONTRACTOR SHALL VISIT THE SITE AND DETERMINE THE EXTENT OF DEMOLITION WORK AND NEW WORK NEEDED FOR THIS PROJECT, PRIOR TO SUBMITTING BID.
- CONTRACTOR SHALL BECOME FAMILIAR WITH THE PROJECT SCOPE, CONSTRAINTS, UTILITY CONNECTIONS, AND BUILDING SERVICES, PRIOR TO SUBMITTING BID.
- CONTRACTOR SHALL GIVE FIRST RIGHT TO REFUSAL OF SALVAGE TO THE OWNER. IF THE OWNER ELECTS TO NOT KEEP SALVAGE, CONTRACTOR SHALL REMOVE SALVAGE BY LAWFUL MEANS.
- DRAWINGS ARE SCHEMATIC AND DIAGRAMMATIC IN NATURE. DRAWINGS SHALL NOT BE SCALED. COORDINATE ROUTING OF SERVICES WITH SITE CONDITIONS AND WITH WORK OF OTHER TRADES.
- FIELD VERIFY DIMENSIONS PRIOR TO ORDERING, FABRICATING, AND ERECTION OF MATERIAL AND/OR EQUIPMENT. NOTIFY THE ENGINEER OF DISCREPANCIES IN A TIMELY MANNER.
- VERIFY CLEARANCE REQUIREMENTS AND ROUTING OF DUCTWORK AND PIPING PRIOR TO FABRICATION, AS MINOR MODIFICATIONS SUCH AS DUCT AND/OR PIPING RISES AND DROP MAY BE REQUIRED DUE TO FIELD CONDITIONS. MAKE MINOR MODIFICATIONS TO THE BUILDING, PIPING, SPRINKLER, DUCTWORK, ELECTRICAL, ETC. AS SHOWN ON THE DRAWINGS OR REQUIRED TO COMPLETE THE INSTALLATION OF A COMPLETED WORKABLE SYSTEM.
- MAINTAIN WEATHER-TIGHT BARRIERS TO PREVENT DAMAGE FROM THE ELEMENTS DURING DEMOLITION AND NEW CONSTRUCTION PERIOD.
- SEAL PENETRATIONS THROUGH THE BUILDING ENVELOPE.
- PENETRATIONS THROUGH RATED WALLS, FLOORS, PARTITIONS AND ASSEMBLIES SHALL BE INSTALLED AND FIRESAFED TO MEET UL FIRE RESISTANCE LISTING AND NFPA REQUIREMENTS FOR THE PENETRATION.
- COORDINATE DEVICES REQUIRING ACCESS PANELS WITH THE ARCHITECT AND OTHER TRADES.
- MAINTAIN MINIMUM CLEARANCE 10'-0" BETWEEN OUTSIDE INTAKES AND EXHAUST OUTLETS AND PLUMBING VENTS.
- COORDINATE FINAL LOCATIONS AND ELEVATIONS WITH THE ARCHITECT PRIOR TO INSTALLATION.
- COORDINATE FINAL FINISH COLORS OF MATERIALS, DEVICES, DIFFUSER, GRILLES, LOUVERS, AND/OR EQUIPMENT WITH THE ARCHITECT PRIOR TO ORDERING, FABRICATION AND INSTALLATION.
- SCHEDULE UTILITY SERVICES SHUTDOWNS WITH OWNER AND ARCHITECT. MINIMIZE DISRUPTIONS AND DOWNTIME TO THE OWNER.
- INSTALL DEVICES AND EQUIPMENT TO MEET ADA REQUIREMENTS.
- ROUTE DUCT AND PIPING CONCEALED IN INTERSTITIAL SPACE UNLESS NOTED OTHERWISE.
- DOCUMENT LOCATIONS OF DEVICES, DUCT, PIPING, AND EQUIPMENT ON "AS-BUILT" RECORD DRAWINGS AS PER THE SPECIFICATIONS.
- PAY FOR SERVICE, DEPOSITS, INSPECTION, AND CONNECTION FEES REQUIRED FOR A COMPLETE INSTALLATION. COORDINATE WITH THE UTILITY SERVICE PROVIDER FOR THE REQUIREMENTS NEEDED FOR THIS PROJECT.
- HVAC SYSTEMS SHALL BE CONSTRUCTED IN ACCORDANCE WITH NFPA 90A AND NFPA 101.
- WORK SHOWN IN THE DRAWINGS SHALL COMPLY WITH APPLICABLE NATIONAL, STATE, AND LOCAL ORDINANCES AND CODES.

meconsulting.co



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee, TX 77656
Silsbee Independent School District
1575 Hwy 96 N


ISSUED FOR SCHEMATIC DESIGN
DATE: _____
DESIGN DEVELOPMENT
DATE: _____
BIDS & CONSTRUCTION
DATE: 3/9/2022
REVISION: _____
DATE: _____
REVISION: _____
DATE: _____
REVISION: _____
DATE: _____

DRAWINGS SHEET TITLE
MECHANICAL LEGEND & NOTES

SHEET NUMBER
M000
21051
PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 • FAX (337) 234-7774
Mechanical Contact: Dustin Duval
dustin@meconsulting.com
Electrical Contact: David Carroll
david@meconsulting.com
PROJECT No.: 21187.00

SAVED: 11:00 AM, 3/9/2022
PROJECT: SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
DRAWING: MECHANICAL LEGEND & NOTES
SHEET: M000
SCALE: AS SHOWN
DATE: 3/9/2022
BY: DUSTIN DUVAL
CHECKED: DAVID CARROLL
APPROVED: _____



36 DROPS, 700 CFM EACH = 25,200 CFM SIZED AT 3,000 FPM.

MECHANICAL NOTES	
1	GALVANIZED SPIRAL DUCT MOUNTED WITH CENTERLINE AT 14'-0" AFF.
2	WALL MOUNTED EXHAUST FAN MOUNTED AT MAXIMUM HEIGHT AFF AND BELOW STRUCTURE.
3	SINGLE PHASE BUILDING AUTOMATION STARTER MOUNTED ON WALL FOR CONTROL OF WALL MOUNTED EXHAUST FAN. PROVIDE AND INSTALL A BLACK LABEL WITH 1" TALL WHITE CAPITAL LETTERS READING "ON/OFF SWITCH FOR AREA VENTILATION FAN".
4	6" THICK REINFORCED CONCRETE HOUSE KEEPING PAD.

ALL EXHAUST DUCT WORK SHALL BE GALVANIZED SPIRAL DUCT AND SHALL BE PER SMACNA CLASS 1, MATERIAL CLASS 26, AND 6"-10" W.C. NEG PRESSURE.
 DUCTWORK SHALL BE JOINED WITH GASKETED FITTINGS. DO NOT USE EXTERNAL MASTIC OR DUCT TAPE UNLESS APPROVED BY LECO.

1 Mechanical Plan
 1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions
 CALLED NORTH

1304 BERTRAND DRIVE SUITE F7
 LAFAYETTE, LOUISIANA 70506
 (337) 234-7474 • FAX (337) 234-7774
 Mechanical Contact: Dustin Duval
 dustin@meconsulting.com
 Electrical Contact: David Carroll
 david@meconsulting.com
 PROJECT No.: 21187.00

AAI
 Architectural Alliance Incorporated
 150 Pine Grove, Suite 200
 Edinger Plaza
 Beaumont, Texas 77701
 Tel: (409) 886-7176
 Fax: (409) 886-7176
 J. HARRINGTON, A.I.A.
 RICHARD JONES, A.I.A.
 www.aaiarchitect.com

STATE OF TEXAS
 DUSTIN W. DUVAL
 117604
 LICENSED PROFESSIONAL ENGINEER
 3/3/2022

SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
 Silsbee Independent School District
 1575 Hwy 96 N
 Silsbee, TX 77656

ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE:	3/9/2022
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE
MECHANICAL PLAN

SHEET NUMBER
M201
 21051
 PROJECT NUMBER

SAVED: PLOAN, KELLY
 LEROUX
 11:01 AM, DATE: 12/14/2021
 PLOT SIZE: ARCH expand D (36.00 x 24.00 inches)

FAN SCHEDULE


UNIT NO.	SERVICE	MIN. CFM	EXT. S.P.	RPM	FAN POWER	TYPE	DRIVE	ELECTRICAL SERVICE	CONTROL	BASIS OF DESIGN
EF-1	WELDING BOOTHS	25200	12"	1800	75 HP	INLINE UP-BLAST	DIRECT	480-3-60	VFD	LINCOLN ELECTRIC M18464-39
EF-2	WELDING ADDITION 102	1720	0.3"	1466	1/2 HP	WALL	DIRECT	120-1-60	FAN STARTER	GREENHECK SE1-16-421-VG

- NOTES:
1. PROVIDE WALL MOUNTED PROPELLER TYPE FAN WITH BMS SINGLE PHASE MOTOR STARTER FOR ON/OFF CONTROL, GRAVITY BACKDRAFT DAMPER, MOTOR SIDE HOUSING WITH WIRE GUARD, WEATHER HOOD AND SPEED CONTROLLER FOR BALANCING.
 2. EF-1: PROVIDE WITH TELESCOPING EXTRACTION ARM KIT, MANUAL BALANCING DAMPER, AND CONNECTION ACCESSORIES FOR EACH WELDING BOOTH AND GRINDING STATION
 3. EF-1: PROVIDE WITH LINCOLN PRISM 20 FILTRATION UNIT, VFD, VFD CONTROLLER, AND FAN SILENCER.

LOUVER SCHEDULE

SYMBOL	SERVICE	BLADE ORIENTATION	BPWP (FPM)	SIZE (W"xH"xD")	DESIGN FLOW (CFM)	FREE AREA MIN (SF)	AIR VEL (FPM)	AIR P.D. (IN. WC)	AMCA 540/550	SCREEN (BIRD/INSECT)	BASIS OF DESIGN
L-1	WELDING SHOP 102	VERTICAL	1250	30"x30"x6"	1720	1.89	910	0.09	540/550	BIRD	RUSKIN EME6325D

- NOTES:
1. LOUVERS SHALL HAVE 70% KYNAR FINISH, COLOR TO BE SELECTED BY ARCHITECT.
 2. LOUVERS AND LOUVER ACCESSORIES TO BE ALUMINUM.
 3. LOUVERS TO MEET AMCA 540/550 RATINGS.
 4. LOUVERS WITHIN METAL PANELS TO BE FULLY FLANGED (NO EXTENDED SILL), ALL OTHER MOUNTING SURFACES TO HAVE CHANNEL FRAME WITH EXTENDED SILLS. REFER TO ARCHITECTURAL ELEVATIONS FOR EXACT BUILDING MATERIALS.



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

Silsbee Independent School District

Silsbee, TX 77656

1575 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN
DATE: _____

DESIGN DEVELOPMENT
DATE: _____

BIDS & CONSTRUCTION
DATE: 3/9/2022

REVISION: _____
DATE: _____

REVISION: _____
DATE: _____

REVISION: _____
DATE: _____

DRAWINGS SHEET TITLE
MECHANICAL SCHEDULES & DETAILS

SHEET NUMBER
M301
21051
PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 • FAX (337) 234-7774

Mechanical Contact: Dustin Duval
dustin@meconsulting.com
Electrical Contact: David Carroll
david@meconsulting.com

PROJECT No.: 21187.00

SAVED: PLOAN, KELLY
LEBOUEF
11:07 AM DATE: 12/14/2021
PLOT SIZE: ARCH expand D (36.00 x 24.00 (inches))

DEFINE

ELECTRICAL ABBREVIATIONS

CT	DENOTES COUNTER-TOP HEIGHT MOUNTED. CONTRACTOR TO VERIFY COUNTER TOP HEIGHT AND HEIGHT OF BACK SPLASH.
E	DENOTES EMERGENCY DEVICE
G	DENOTES GROUND FAULT INTERRUPTER PROTECTED
WP	DENOTES WEATHERPROOF
AFF	DENOTES ABOVE FINISHED FLOOR
C	DENOTES CONDUIT
A	DENOTES AMP
EWC	ELECTRICAL WATER COOLER
W	WALL MOUNTED-48" ABOVE FINISHED FLOOR OR AS NOTED
CB	CODE BLUE
IG	DENOTES ISOLATED GROUND
FDS	FUSED DISCONNECT SWITCH
BOF	BOTTOM OF FIXTURE
MRR	MANUFACTURER'S RECOMMENDED RATING
WR	WEATHER RESISTANT
VOU	VERIFY ON JOB
VR	VANDAL RESISTANT
SPD	SURGE PROTECTION DEVICE - REFER TO SPECIFICATIONS.

ELECTRICAL LINE TYPE LEGEND

	SCREENED LINES/SYMBOLS INDICATE EXISTING DEVICES TO REMAIN.
	DASHED LINES/SYMBOLS INDICATE EXISTING DEVICES TO BE REMOVED OR RELOCATED.
	BOLD LINES/SYMBOLS INDICATE NEW OR RELOCATED DEVICES.

DESIGN

ELECTRICAL LEGEND

LIGHTING DESCRIPTION		SPECIAL SYSTEMS DESCRIPTION	
	LIGHTING FIXTURE-REFER TO LIGHTING FIXTURE SCHEDULE		COMMUNICATIONS OUTLET - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 1" CONDUIT TO ACCESSIBLE CEILING (18" A.F.F. OR AS NOTED) - PROVIDE A BLANK PLATE OR XX DENOTES CABLE TYPE AND QUANTITY; P=PHONE, D=DATA, C=COAX REFER TO SPECIFICATIONS
	LIGHTING FIXTURE-REFER TO LIGHTING FIXTURE SCHEDULE		TELEVISION OUTLET-DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 1" C. TO ACCESSIBLE CEILING (VERIFY MOUNTING HEIGHT AND LOCATION WITH ARCHITECT) - PROVIDE BLANK PLATE OR XX DENOTES CABLE TYPE AND QUANTITY; P=PHONE, D=DATA, C=COAX REFER TO SPECIFICATIONS
	LIGHTING FIXTURE-REFER TO LIGHTING FIXTURE SCHEDULE		TELEVISION OUTLET-DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 1" C. TO ACCESSIBLE CEILING (VERIFY MOUNTING HEIGHT AND LOCATION WITH ARCHITECT) - PROVIDE BLANK PLATE OR XX DENOTES CABLE TYPE AND QUANTITY; P=PHONE, D=DATA, C=COAX REFER TO SPECIFICATIONS
	LIGHTING FIXTURE-REFER TO LIGHTING FIXTURE SCHEDULE		TELEVISION OUTLET-DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 1" C. TO ACCESSIBLE CEILING (VERIFY MOUNTING HEIGHT AND LOCATION WITH ARCHITECT) - PROVIDE BLANK PLATE OR XX DENOTES CABLE TYPE AND QUANTITY; P=PHONE, D=DATA, C=COAX REFER TO SPECIFICATIONS
	CEILING MOUNTED EXIT LIGHT - REFER TO LIGHTING FIXTURE SCHEDULE - ARROWS DEFINE DIRECTION		DATA JACK ABOVE CEILING W/ 30" OF SLACK (FUTURE WIRELESS ACCESS POINT) XX - DENOTES CABLE QUANTITY
	WALL MOUNTED EXIT LIGHT - COORDINATE FINAL MOUNTING HEIGHT WITH THE ARCHITECT - REFER TO LIGHTING FIXTURE SCHEDULE - ARROWS DEFINE DIRECTION		AUDIO & VISUAL - DEEP 4" SQUARE DEEP DOUBLE GANG BOX WITH DOUBLE GANG PLASTER RING (MOUNT 18" A.F.F. V.O.J.) WITH 1 1/4" CONDUIT WITH CABLE/PULLSTRING TO A MINIMUM OF 6" ABOVE CEILING.
	EMERGENCY LIGHT (8'-0" A.F.F. OR AS NOTED) - REFER TO LIGHTING FIXTURE SCHEDULE		OVERHEAD PROJECTOR - DEEP 4" SQUARE BOX INSTALLED ABOVE CEILING ADJACENT TO OVERHEAD PROJECTOR (SEE DETAIL)
	CEILING MOUNTED EGRESS LIGHT - REFER TO LIGHTING FIXTURE SCHEDULE		AUDIO & VISUAL - RECESSED FLOOR BOX - WIREMOLD RFB9 OR EQUAL (SEE DETAIL)
	PHOTOCCELL		SMART BOARD J-BOX - 4" SQUARE DEEP BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING. (SEE DETAIL)
	SINGLE POLE TOGGLE SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)		CONTROL STATION - 4" SQUARE DEEP BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING. (SEE DETAIL)
	THREE-WAY TOGGLE SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)	FIRE ALARM DESCRIPTION	
	WALL MOUNTED DIMMER SWITCH WITH ON/OFF AND 0-10V OUTPUT DIMMING. DIMMER MUST BE COMPATIBLE WITH BALLAST OR LED. REFER TO SPECIFICATIONS. PROVIDE ALL NECESSARY CONDUCTORS FOR COMPLETE OPERATING SYSTEM. (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)		FIRE ALARM PULL STATION - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE IN 3/4" CONDUIT TO ACCESSIBLE CEILING (48" A.F.F. TO CENTER OF DEVICE)
	MOTOR RATED SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED). CONTRACTOR TO PROVIDE SWITCH TO DE-ENERGIZE EACH CURRENT CARRYING CONDUCTOR. LOCATE ADJACENT TO EQUIPMENT BEING SERVED IN A READILY ACCESSIBLE LOCATION.		FIRE ALARM VALVE SUPERVISORY SWITCH- PROVIDE MONITORING MODULE FOR ALL VALVE SUPERVISORY SWITCHES, COORDINATE REQUIREMENTS, QUANTITIES, AND LOCATIONS WITH THE SPRINKLER CONTRACTOR
	SINGLE POLE KEYED SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)		FIRE ALARM FLOW DETECTOR/SWITCH - PROVIDE MONITORING MODULE FOR ALL FLOW DETECTORS/SWITCHES, COORDINATE REQUIREMENTS, QUANTITIES, AND LOCATIONS WITH THE SPRINKLER CONTRACTOR
	SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED) COORDINATE TYPE AND INSTALLATION REQUIREMENTS WITH MANUFACTURE. COORDINATE LOCATION WITH OWNER.		MAGNETIC DOOR HOLDER - CONTRACTOR TO CONNECT TO 120V CIRCUIT. DOOR HOLDERS SHALL RELEASE UPON ACTIVATION OF THE FIRE ALARM SYSTEM
	SINGLE POLE SWITCH. MOUNT IN DOOR SWING. LEE ELECTRIC: 210DN		FIRE ALARM CONTROL PANEL
	INBOARD AND OUTBOARD SWITCHING UNLESS NOTED OTHERWISE (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)		FIRE ALARM ANNUNCIATOR PANEL - BACK BOX WITH 1" CONDUIT MINIMUM TO ACCESSIBLE CEILING
	SINGLE POLE DIGITAL PRESET COUNT DOWN TYPE TIMER SWITCH (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED) SENSORSWITCH PTS 60 OR EQUAL		SMOKE DETECTOR - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE IN 3/4" CONDUIT TO ACCESSIBLE CEILING.
	WALL MOUNTED OCCUPANCY SENSOR (48" AFF TO CENTER OF DEVICE OR AS NOTED) - REFER TO SPECIFICATIONS.		SINGLE STATION SMOKE DETECTOR 120 VOLT WITH BATTERY BACKUP AND INTERCONNECTED TO ALL SMOKE DETECTORS IN UNIT.
	WALL MOUNTED DOUBLE SWITCH OCCUPANCY SENSOR (48" AFF TO CENTER OF DEVICE OR AS NOTED) - REFER TO SPECIFICATIONS.		FIRE ALARM DUCT DETECTOR
	CORNER MOUNTED OCCUPANCY SENSOR - MOUNTING HEIGHT TO BE DETERMINED PER MANUFACTURER'S RECOMMENDATIONS FOR OPTIMAL COVERAGE - MYTECH, WAIT STOPPER		HEAT DETECTOR - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE IN 3/4" CONDUIT TO ACCESSIBLE CEILING.
POWER DESCRIPTION			ADDRESSABLE INPUT/OUTPUT MODULE
	DUPLEX CONVENIENCE OUTLET (18" A.F.F. FOR GENERAL AREAS, 36" A.F.F. FOR GARAGES, HANGARS AND THE LIKE OR AS NOTED)		FIRE ALARM WALL MOUNTED STROBE UNIT - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE IN 3/4" CONDUIT TO ACCESSIBLE CEILING (MOUNTING HEIGHT AS PER NFPA 72. ALL DEVICES SHALL BE AT SAME HEIGHT) XX DENOTES CANDELA RATING
	TELEVISION OUTLET (VERIFY MOUNTING HEIGHT AND LOCATION WITH ARCHITECT)		FIRE ALARM CEILING MOUNTED STROBE - XX DENOTES CANDELA RATING
	ELECTRICAL WATER COOLER, COORDINATE ELECTRICAL DEVICE/OUTLET TYPE AND LOCATION WITH PLUMBING CONTRACTOR (CONCEAL OUTLET/DEVICE BEHIND COOLER) OUTLET TO BE GROUND FAULT INTERRUPTER PROTECTED.		FIRE ALARM WALL MOUNTED AUDIBLE/VISUAL DEVICE - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE IN 3/4" CONDUIT TO ACCESSIBLE CEILING (MOUNTING HEIGHT AS PER NFPA) XX DENOTES CANDELA RATING
	MICROWAVE OUTLET - RECESSED 20 AMP DUPLEX OUTLET. HUBBELL OR EQUAL. VERIFY EXACT MOUNTING LOCATION WITH OWNER/ARCHITECT PRIOR TO ROUGH IN.		FIRE ALARM CEILING MOUNTED AUDIBLE/VISUAL DEVICE - XX DENOTES CANDELA RATING
	WATER HEATER. COORDINATE ELECTRICAL OUTLET/DISCONNECT TYPE AND LOCATION WITH PLUMBING CONTRACTOR	SECURITY SYSTEM DESCRIPTION	
	SMART BOARD OUTLET - SB DENOTES HEIGHT OF OUTLET PER OWNER		SURVEILLANCE CAMERA - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING. VERIFY HEIGHT WITH ENGINEER.
	DUPLEX CONVENIENCE OUTLET (18" A.F.F. OR AS NOTED) TR DENOTES TAMPER RESISTANT - HUBBELL: RR205TR, GFTR20 OR EQUAL		CARD READER - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING (48" A.F.F. TO CENTER OF DEVICE OR AS NOTED)
	COMBINATION RECEPTACLE/OUTLET AND DUAL USB CHARGER - LEVITON T5832 OR EQUAL (18" A.F.F. OR AS NOTED)		SECURITY SYSTEM MOTION DETECTOR - LONG RANGE - COORDINATE ROUGH-IN REQUIREMENTS WITH SECURITY SYSTEM PROVIDER.
	DOUBLE DUPLEX CONVENIENCE OUTLET (18" A.F.F. OR AS NOTED)		SECURITY SYSTEM MOTION DETECTOR - WIDE RANGE - COORDINATE ROUGH-IN REQUIREMENTS WITH SECURITY SYSTEM PROVIDER.
	SPECIAL OUTLET (VERIFY TYPE AND MOUNTING HEIGHT WITH EQUIPMENT MANUFACTURE)		SECURITY SYSTEM KEY PAD - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING
	COUNTER TOP DUPLEX OUTLET (CLEAR BACK SPLASH)		SECURITY SYSTEM DOOR CONTACT - COORDINATE ROUGH-IN REQUIREMENTS WITH SECURITY SYSTEM PROVIDER.
	CEILING MOUNTED CORD REEL OUTLET - HUBBELL #HBL45123C20 OR APPROVED EQUAL		SECURITY SYSTEM HORN - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING.
	MOTOR STARTER - PROVIDED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR.	NOTES:	
	FLOOR BOX, POWER (COORDINATE FINAL LOCATION WITH OWNER/ARCHITECT PRIOR TO INSTALLATION) MINIMUM 2-3/4" CONDUITS TO ACCESSIBLE CEILING.	1. ITEMS ON THIS SCHEDULE ARE NOT NECESSARILY SHOWN ON PLANS.	
	FLOOR BOX, COMBINATION POWER/COMMUNICATIONS (COORDINATE FINAL LOCATION WITH OWNER/ARCHITECT PRIOR TO INSTALLATION. 2-1" CONDUITS IN SLAB TO 6" ABOVE ACCESSIBLE CEILING - PROVIDE BLANK PLATE OR XX DENOTES CABLE TYPE AND QUANTITY; P=PHONE, D=DATA, C=COAX REFER TO SPECIFICATIONS		
	JUNCTION BOX		
	CONTROL POWER FOR ENERGY MANAGEMENT SYSTEM - PROVIDE OUTLET OR JUNCTION BOX AT LOCATION PER EMS CONTRACTOR		
	HAND DRYER - COORDINATE OUTLET/DEVICE TYPE WITH SUPPLIER. COORDINATE LOCATION WITH THE OWNER/ARCHITECT PRIOR TO ROUGH-IN.		
	ELECTRICAL MOTOR (COORDINATE TERMINATION WITH SUPPLIER)		
	FUSED DISCONNECT SWITCH - FUSE AT MANUFACTURE RECOMMENDED RATING UNLESS NOTED OTHERWISE. XX DENOTES DISCONNECT SIZE, Y DENOTES PHASE, ZZ ZF DENOTES FUSE SIZE.		
	ELECTRICAL PANEL SURFACE MOUNTED		
	ELECTRICAL PANEL FLUSH MOUNTED		
	TELEPHONE/POWER POLE: COORDINATE EXACT MOUNTING LOCATION WITH FURNITURE MANUFACTURE. MAKE FINAL CONNECTIONS. REFER TO DETAIL. WIRE MOLD: 30TP-4V		
	CONDUIT RUN CONCEALED IN WALL OR ABOVE CEILING		
	CONDUIT RUN CONCEALED UNDER FLOOR OR BELOW GRADE		
	HOMERUN TO ELECTRIC PANEL BOARD (INDICATED NUMBER OF CIRCUIT BY NUMBER OF ARROWS)		
	THREE (3) CONDUCTORS RUN IN CONDUIT. EVERY CIRCUIT TO HAVE A GROUND, SHARED NEUTRAL IS NOT ALLOWED.		
	FOUR (4) CONDUCTORS RUN IN CONDUIT. EVERY CIRCUIT TO HAVE A GROUND, SHARED NEUTRAL IS NOT ALLOWED.		
	FIVE (5) CONDUCTORS RUN IN CONDUIT. EVERY CIRCUIT TO HAVE A GROUND, SHARED NEUTRAL IS NOT ALLOWED.		
	FOUR (4) CONDUCTORS RUN IN CONDUIT, ONE CONDUCTOR DESIGNATED FOR ISOLATED GROUND		
	MOTORIZED DAMPER - PROVIDE BY OTHERS. ELECTRICALLY POWERED BY ELECTRICAL CONTRACTOR WHEN NOTED.		
	START - STOP STATION - COORDINATE WITH EQUIPMENT PROVIDER.		
	VARIABLE FREQUENCY DRIVE PROVIDED BY MECHANICAL AND INSTALLED BY ELECTRICAL. MAINTAIN CLEARANCES PER NFPA 70		
INTERCOM DESCRIPTION			
	CLOCK, D=DENOTES DOUBLE FACE, S=DENOTES SINGLE FACE - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING		
	WALL MOUNTED SPEAKER - PROVIDE SPEAKER BACK BOX AND CABLING IN 3/4" CONDUIT TO ACCESSIBLE CEILING SPACE		
	INTERCOM CONTROL STATION - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING.		
	TRUMPET SPEAKER - DEEP 4" SQUARE BOX WITH SINGLE GANG PLASTER RING WITH CABLE/PULLSTRING IN 3/4" CONDUIT TO ACCESSIBLE CEILING. VERIFY HEIGHT WITH ENGINEER.		

DELIVER


ELECTRICAL GENERAL NOTES

- ELECTRICAL INSTALLATION SHALL BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE NATIONAL ELECTRICAL CODE (NEC) AS WELL AS ANY LOCAL CODES AND ORDINANCES.
- MAINTAIN PROPER WORKING SPACE CLEARANCES ABOUT ELECTRICAL EQUIPMENT PER NEC ARTICLE 110.26.
- FULLY COORDINATE ALL ELECTRICAL REQUIREMENTS OF EQUIPMENT BEING FURNISHED BY ALL DIVISIONS UNDER THIS CONSTRUCTION CONTRACT. EACH SYSTEM SHALL BE COMPLETE AND FULLY FUNCTIONAL. THIS INCLUDES MECHANICAL, PLUMBING, OWNER PROVIDED AND CONTRACTOR PROVIDED EQUIPMENT. CONTRACTOR TO REFER TO EQUIPMENT INSTALLATION DOCUMENTS AND SHOP DRAWINGS PRIOR TO ANY ROUGH-IN.
- CONTRACTOR SHALL COORDINATE CIRCUIT BREAKER AND FUSE SIZES FOR MECHANICAL EQUIPMENT PER SUBMITTED EQUIPMENT MANUFACTURER'S RECOMMENDED NAMEPLATE RATINGS PRIOR TO SHOP DRAWING PHASE OF PROJECT.
- INTERRUPTION OF SERVICE: BEFORE ANY EQUIPMENT IS SHUT DOWN FOR DISCONNECTING OR TIE-INS. ARRANGEMENTS SHALL BE MADE WITH THE ARCHITECT AND THIS WORK SHALL BE DONE AT THE TIME BEST SUITED TO THE OWNER. OUTAGES MUST BE SCHEDULED THROUGH THE ARCHITECT. THE ARCHITECT SHALL REVIEW EXTENT, LENGTH, AND TIMING OF OUTAGES. SERVICES SHALL BE RESTORED THE SAME DAY. PROVIDE TEMPORARY POWER OR OTHER SERVICES AS REQUIRED DURING OUTAGES. ALL OVERTIME OR PREMIUM COSTS ASSOCIATED WITH THIS WORK SHALL BE INCLUDED IN THE BASE BID.
- COORDINATE LOCATION OF ELECTRICAL EQUIPMENT WITH PIPES AND DUCT WORK BEING SUPPLIED BY OTHER DIVISIONS. THE EQUIPMENT SPACE INCLUDED ALL REFERENCED NEC CLEARANCES SHALL BE MAINTAINED. IF ANY PIPES OR DUCT WORK VIOLATE ANY ELECTRICAL CLEARANCE REQUIREMENTS, IT SHALL BE REMOVED AND RELOCATED AT THE CONTRACTOR'S EXPENSE. DRIP PANS ARE NOT PERMITTED UNLESS SPECIFICALLY CALLED FOR IN THE CONSTRUCTION DOCUMENTS.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO SEE THAT ALL EQUIPMENT THAT MAY REQUIRE MAINTENANCE AND OPERATION ARE READILY ACCESSIBLE, REGARDLESS OF THE DIAGRAMMATIC LOCATION SHOWN ON THE DRAWINGS. ALL CONNECTIONS TO FIXTURES AND EQUIPMENT SHOWN ON THE DRAWINGS SHALL BE CONSIDERED DIAGRAMMATIC UNLESS OTHERWISE INDICATED BY A SPECIFIC DETAIL ON THE DRAWINGS. THE ACTUAL CONNECTIONS SHALL BE MADE TO FULLY SUIT THE REQUIREMENTS OF EACH CASE AND ADEQUATELY PROVIDE FOR SERVICING.
- CONTRACTOR SHALL TAMP AND BACKFILL ALL TRENCHES. TRENCHES SHALL BE LEVEL WITH FINISH GRADE.
- CONTRACTOR SHALL VISIT THE SITE AND DETERMINE THE EXTENT OF DEMOLITION WORK AND NEW WORK NEEDED FOR THIS PROJECT.
- CONTRACTOR SHALL BECOME FAMILIAR WITH THE PROJECT SCOPE, CONSTRAINTS, UTILITY CONNECTIONS, AND BUILDING SERVICES.
- CONTRACTOR SHALL GIVE FIRST RIGHT TO REFUSAL OF SALVAGE TO THE OWNER, IF THE OWNER ELECTS TO NOT KEEP SALVAGE, CONTRACTOR SHALL REMOVE SALVAGE BY LAWFUL MEANS.
- DRAWINGS ARE SCHEMATIC AND DIAGRAMMATIC IN NATURE. DRAWINGS SHALL NOT BE SCALED. COORDINATE ROUTING OF SERVICES WITH SITE CONDITIONS AND WITH WORK OF OTHER TRADES.
- FIELD VERIFY DIMENSIONS PRIOR TO ORDERING, FABRICATING, AND ERECTION OF MATERIAL AND/OR EQUIPMENT. NOTIFY THE ENGINEER OF DISCREPANCIES IN A TIMELY MANNER.
- SEAL PENETRATIONS THROUGH THE BUILDING ENVELOPE.
- PENETRATIONS THROUGH RATED WALLS, FLOORS, PARTITIONS AND ASSEMBLIES SHALL BE INSTALLED AND FIRESAFED TO MEET UL FIRE RESISTANCE LISTING AND NFPA REQUIREMENTS FOR THE PENETRATION.
- COORDINATE DEVICES REQUIRING ACCESS PANELS WITH THE ARCHITECT AND OTHER TRADES.
- DEVICE SYMBOLS ALONG WITH DRAWINGS, DRAWING NOTES, AND SPECIFICATIONS ARE INTENDED TO PROVIDE A COMPLETE SYSTEM. CONTRACTOR TO COORDINATE WITH ALL TRADES TO PROVIDE A COMPLETE SYSTEM.

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 • FAX (337) 234-7774

Mechanical Contact: Dustin Duval
Electrical Contact: David Carroll
dustin@meconsulting.com
david@meconsulting.com

CONSULTING PROJECT No.: 21187.00



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

Slisbee Independent School District

1575 Hwy 96 N
Slisbee, TX 77666

ISSUED FOR SCHEMATIC DESIGN

DESIGN DEVELOPMENT

BIDS & CONSTRUCTION

DATE: 3/9/2022

REVISION: DATE: _____

REVISION: DATE: _____


REVISION: DATE: _____

DRAWINGS SHEET TITLE
ELECTRICAL LEGEND


SHEET NUMBER
E000
PROJECT NO. 21051
PROJECT NUMBER

SAVED: 11:00 AM
 PROJECT: 21051
 USER: JLD
 DATE: 12/14/2021
 SHEET: E000
 PROJECT: ARCH - expansion D (36,00 x 24,00) (rev01)

SAVED: PLOAN, KELLY, LEROUEFF, TLOU, DATE: 12/14/2021, 2:41:00, BHEET SIZE: ARCH expand D (36.00 x 24.00 (inches))



1 Electrical Demolition Plan
1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions



- GENERAL ELECTRICAL DEMOLITION NOTES:**
1. THE CONTRACTOR IS ALLOWED TO RE-USE EXISTING DEVICES, DISCONNECTS, & PANELS IF THE EQUIPMENT IS IN GOOD WORKING CONDITION. THE CONTRACTOR SHALL CLEAN & REPAIR THE EXISTING DEVICES AS NEEDED IF THE CONTRACTOR CHOOSES TO RE-USE.
 2. REMOVE EXISTING LIGHT FIXTURES, DISCONNECTS, OUTLETS, BOXES, WIRING, CONDUIT, ETC. AND OFFER TO OWNER. IF OWNER REFUSES, ELECTRICAL CONTRACTOR SHALL REMOVE FROM SITE AND PROPERLY AND LEGALLY DISPOSE.
 3. REMOVE PANELS, ASSOCIATED CIRCUITS, AND FEEDER.
 4. REMOVE EXISTING DEVICES FROM WALLS BEING DEMOLISHED. IF THEY OCCUR IN THE MIDDLE OF A CIRCUIT, MAKE THE REMAINDER OF THE CIRCUIT CONTINUOUS.
 5. RELOCATE EXISTING DEVICE AND EXTEND EXISTING CIRCUITRY.
 6. MAINTAIN ALL REMAINING EXISTING CIRCUITS WHERE INTERRUPTED BY DEMOLITION WORK. PROVIDE WIRING AND CONDUIT TO RESTORE CONTINUOUS CIRCUIT INTEGRITY.
 7. PROTECT EXISTING ELECTRICAL EQUIPMENT AND INSTALLATIONS INDICATED TO REMAIN. IF DAMAGED OR DISTURBED IN THE COURSE OF THE WORK, REMOVE DAMAGED PORTIONS AND INSTALL NEW PRODUCTS OF EQUAL CAPACITY, QUALITY, AND FUNCTIONALITY.
 8. CONTACT TEXAS ONE CALL FOR IDENTIFICATION OF ALL UNDERGROUND UTILITIES PRIOR TO REMOVAL.
 9. EXISTING ROUTING OF CIRCUITS/FEEDERS ARE INDICATED ON DRAWINGS FOR REFERENCE ONLY. CONTRACTOR IS RESPONSIBLE FOR VERIFYING EXACT LOCATIONS OF FEEDERS/CIRCUITS PRIOR TO ANY EXCAVATION. CONTRACTOR SHALL BARE ALL COST OF RESTORING EXISTING ELECTRICAL FUNCTIONALITY SHOULD ANY EXISTING UNDERGROUND ELECTRICAL UTILITIES BE DAMAGED DURING THE COURSE OF CONSTRUCTION.

AAI Architectural Alliance Incorporated

150 Pine Street, Suite 200
Edison Plaza
Blossington, Texas 77701
Tel: (409) 386-7176
Fax: (409) 386-7176
www.aaiinc.com

DAVID CARROLL
137373
LICENSED PROFESSIONAL ENGINEER
3/3/2022

SILSBBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

Silsbee, TX 77656

Silsbee Independent School District

1575 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/9/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE

ELECTRICAL DEMOLITION PLAN

SHEET NUMBER

E100

21051

PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 • FAX (337) 234-7774


Mechanical Contact: Dustin Duval
dustin@meconsulting.com
Electrical Contact: David Carroll
david@meconsulting.com

PROJECT No.: 21187.00


LIGHTING FIXTURE SCHEDULE							
TYPE MARK	DESCRIPTION	LAMP		VOLTS	MANUFACTURER	MODEL	COMMENTS
		No.	TYPE				
B2	4' LED LOW BAY	-	LED	277	LITHONIA	UFIT-L48-10000LM-SEF-MVOLT-GZ10-40K-80CRI	
B2E	4' LED LOW BAY W/ BATTERY BACKUP	-	LED	277	LITHONIA	UFIT-L48-10000LM-SEF-MVOLT-GZ10-40K-80CRI; ILB-CP10-HE-A	
E1	EMERGENCY LED WALL LIGHT	-	LED	277	LITHONIA	AFB-OEL-FINISH-UVOLT-N-WT	FINISH TO BE SELECTED BY ARCHITECT
E2	EMERGENCY LED WALL LIGHT	-	LED	277	LITHONIA	ELM4L-FINISH-UVOLT	FINISH TO BE SELECTED BY ARCHITECT
EX	EXISTING FIXTURE TO BE RE-USED						
W1	EXTERIOR LED WALL LIGHT	-	LED	277	LITHONIA	TWX1-ALO-40K-MVOLT-FINISH	FINISH TO BE SELECTED BY ARCHITECT
X1	SINGLE FACE EXIT LIGHT	-	LED	277	LITHONIA	LE-S-1-R-EL N	

GENERAL LIGHTING NOTES:
 1.) HATCHED FIXTURES INDICATE EMERGENCY BATTERY PACK FIXTURES. CIRCUIT BATTERY PACKS AHEAD OF SWITCHES.


LIGHTING NOTES	
1	EXISTING FIXTURE TO BE RE-USED.
2	TIE TO EXISTING EXTERIOR LIGHTING CIRCUIT.
3	1/2" CONDUIT WITH 3#12 TO EXISTING LIGHTING CIRCUIT IN THIS AREA.
4	1/2" CONDUIT WITH 3#12 TO SPARE 20/1 BREAKER IN PANEL "H3A"



1 Lighting Plan
 1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions



SAVED: P:\0000\1214\1214.dwg
 PLOTTED: 12/14/2021
 PLOT DATE: 12/14/2021
 PLOT TIME: 10:24:00
 PLOT SIZE: ARCH expanded D (36.00 x 24.00 inches)



SILSBBEE HIGH SCHOOL WELDING SHOP FINISH-OUT

Silsbee Independent School District

Silsbee, TX 77656

1575 Hwy 96 N


ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/9/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE
LIGHTING PLAN


SHEET NUMBER
E201
 21051
 PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
 LAFAYETTE, LOUISIANA 70506
 (337) 234-7474 • FAX (337) 234-7774
 Mechanical Contact: Dustin Duval
 dustin@meconsulting.com
 Electrical Contact: David Carroll
 david@meconsulting.com
 PROJECT No.: 21187.00

SAVED: P:\0000\1214\2021\1214\1214.dwg
 PLOTTED: 12/14/2021 2:43:00
 PLOT DATE: 12/14/2021
 PLOT TIME: 2:43:00
 PLOT SIZE: ARCH expanded D (36.00 x 24.00 inches)



① Power & Special Systems Plan
 1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions




GENERAL ELECTRICAL NOTES:

- CONTRACTOR SHALL VERIFY FINAL LOCATIONS AND MOUNTING HEIGHTS OF RECEPTACLES LOCATED IN AND AROUND THE WELDING BOOTHS WITH THE WELDING INSTRUCTOR.
- CONTRACTOR SHALL VERIFY FINAL LOCATIONS OF ALL CEILING MOUNTED CORD REEL OUTLETS WITH THE WELDING INSTRUCTOR.
- FURNISH AND INSTALL INTERCOM SPEAKERS AS SHOWN ON DRAWING INCLUDING ALL CABLING AND ACCESSORIES REQUIRED TO INTEGRATE WITH EXISTING SCHOOL INTERCOM/PAGING SYSTEM. SPEAKERS SHALL MATCH EXISTING AND/OR BE COMPATIBLE WITH EXISTING SYSTEM. CONTACT OWNER'S INTERCOM SYSTEM VENDOR.
- FURNISH AND INSTALL FIRE ALARM DEVICES AS SHOWN AND AS PER STATE AND LOCAL CODES INCLUDING CABLING AND ACCESSORIES REQUIRED TO INTEGRATE WITH EXISTING FIRE ALARM SYSTEM. DEVICES SHALL BE COMPATIBLE WITH EXISTING FIRE ALARM SYSTEM. CONTACT OWNER'S FIRE ALARM SYSTEM VENDOR.

ELECTRICAL NOTES

- MODIFY HEIGHT OF EXISTING HORN STROBE TO BE HIGHER THAN LOCKERS OF THIS AREA BUT NO HIGHER THAN 96"
- INSTALL 3/4" CONDUIT WITH #4 CU BONDING JUMPERS TO BOND WELDING BOOTHS AND METAL WELDING EXHAUST DUCT TO SYSTEM GROUND.



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
 Silsbee, TX 77656
 Slisbee Independent School District
 1575 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/9/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	


DRAWINGS SHEET TITLE
POWER & SPECIAL SYSTEMS PLAN

SHEET NUMBER
E301
 21051
 PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
 LAFAYETTE, LOUISIANA 70506
 (337) 234-7474 • FAX (337) 234-7774
 Mechanical Contact: Dustin Duval
 dustin@meconsulting.com
 Electrical Contact: David Carroll
 david@meconsulting.com
 PROJECT No.: 21187.00

ELECTRICAL NOTES

- 1 RE-FEED EXISTING CONDENSING UNIT DISCONNECTS FROM NEW PANEL "M"



1 Mechanical Power Plan
1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 • FAX (337) 234-7774
Mechanical Contact: Dustin Duval
dustin@meconsulting.com
Electrical Contact: David Carroll
david@meconsulting.com
PROJECT No.: 21187.00

AAI
Architectural Alliance Incorporated
150 Pine Grove, Suite 200
Edison Plaza
Bismarck, Texas 77701
(936) 756-7100
FAX (936) 756-7101
www.aaiinc.com

STATE OF TEXAS
DAVID CARROLL
137373
LICENSED PROFESSIONAL ENGINEER
3/3/2022

SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
Silsbee, TX 77656
Silsbee Independent School District
1575 Hwy 96 N

ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE: 3/9/2022	
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE
MECHANICAL POWER PLAN

SHEET NUMBER
E401
21051
PROJECT NUMBER

SAVED: P:\0000\KELLY...
PROJECT: K...
DATE: 12/14/2021
DRAWN BY: ARCH...
SCALE: 1/8" = 1'-0"
CALLS NORTH

DEFINE

PLUMBING & SPRINKLER ABBREVIATIONS

AD	ACCESS DOOR	HP	HORSE POWER
ADA	AMERICANS WITH DISABILITIES ACT	HS	HOSE STATION
AFF	ABOVE FINISHED FLOOR	HW	HAND WASH
AV	ACID VENT	ICE	ICE MACHINE WATER CONNECTION
AW	ACID WASTE	L	LAVATORY
BOP	BOTTOM OF PIPE	LS	LIFT STATION (SANITARY SEWER)
BP	BACKFLOW PREVENTER	MH	MANHOLE
BT	BATH TUB	MV	MIXING VALVE
BTUH	BRITISH THERMAL UNITS PER HOUR	N.O.	NORMALLY OPEN
C	CONDENSATE DRAIN LINE	N.C.	NORMALLY CLOSED
CA	COMPRESSED AIR LINE	NTS	NOT TO SCALE
CB	CATCH BASIN	P	PUMP
CFM	CUBIC FEET PER MINUTE	PIV	POST INDICATING VALVE
CI	CAST IRON	PRV	PRESSURE REDUCING VALVE
CO	CLEANOUT	PSIG	POUNDS PER SQUARE INCH GAGE
CSS	CLINIC SERVICE SINK	PT	PLASTER TRAP
CP	CIRCULATING WATER PUMP	REF	REFRIGERATOR WATER CONNECTION BOX
D	DRAIN LINE	RD	ROOF DRAIN
DF	DRINKING FOUNTAIN	RPM	REVOLUTIONS PER MINUTE
DCW	DOMESTIC COLD WATER LINE	SAN	SANITARY SEWER
DHR	DOMESTIC HOT WATER RETURN LINE	SD	STORM DRAIN
DHW	DOMESTIC HOT WATER LINE	SF	SQUARE FOOT
DS	DRENCH SHOWER	SH	SHOWER
DSEW	DRENCH SHOWER WITH EYE WASH	SK	SINK
DT	DILUTION TRAP	SMH	SEWER MANHOLE
DW	DISHWASHER	SS	SERVICE SINK
ET	EXPANSION TANK	STP	SEWER TREATMENT PLANT
EW	EYE WASH	TD	TRENCH DRAIN
EWC	ELECTRIC WATER COOLER	TP	TRAP PRIMER
EWH	ELECTRIC WATER HEATER	TYP	TYPICAL
FCO	FLOOR CLEANOUT	U	URINAL
FD	FLOOR DRAIN	UNO	UNLESS NOTED OTHERWISE
FDC	FIRE DEPARTMENT CONNECTION	V	VENT
FFE	FINISHED FLOOR ELEVATION	VAC	VACUUM
FH	FIRE HYDRANT	VB	VACUUM BREAKER
FS	FLOOR SINK	VTR	VENT THRU ROOF
GD	GARBAGE DISPOSAL	W	WASHER WATER/RAIN CONNECTION LINE
GPH	GALLONS PER HOUR	WC	WATER CLOSET
GPM	GALLONS PER MINUTE	WCO	WALL CLEANOUT
GT	GREASE TRAP	WF	WASH FOUNTAIN
GWH	GAS FIRED WATER HEATER	WG	WATER GAGE
HB	HOSE BIB	WP	WHIRL POOL
HD	HUB DRIAN	ZVB	ZONE VALVE BOX (MEDICAL GAS)

DESIGN

PLUMBING & SPRINKLER LEGEND

PIPING				VALVES			
EXISTING	DEMO	NEW	DESCRIPTION	EXISTING	DEMO	NEW	DESCRIPTION
---	---DCW---	---	DOMESTIC COLD WATER LINE	---	---	---	BALL VALVE (SHUT-OFF)
---	---DHW---	---	DOMESTIC HOT WATER LINE (110°)	---	---	---	BALL VALVE (SHUT-OFF)
---	---DHR---	---	DOMESTIC HOT WATER RETURN LINE	---	---	---	SHUT-OFF VALVE IN CAST IRON VALVE BOX
---(X°F)---	---(X°F)---	---(X°F)---	DOMESTIC HOT WATER LINE (X-TEMP.)	---	---	---	CALIBRATED BALANCING VALVE
---	---	---	SANITARY SEWER LINE (SAN)	---	---	---	CHECK VALVE
--- V ---	--- V ---	--- V ---	SANITARY SEWER VENT LINE	---	---	---	OS&Y VALVE
---SD---	---SD---	---SD---	STORM DRAIN LINE (PRIMARY)	---	---	---	GAS COCK
---OSD---	---OSD---	---OSD---	OVERFLOW STORM DRAIN LINE (SECONDARY)	---	---	---	BUTTERFLY VALVE
--- C ---	--- C ---	--- C ---	CONDENSATE DRAIN LINE	---	---	---	VALVE IN RISE
---GW---	---GW---	---GW---	GREASE WASTE DRAIN LINE	---	---	---	2-WAY CONTROL VALVE
---AW---	---AW---	---AW---	ACID WASTE DRAIN LINE	---	---	---	3-WAY CONTROL VALVE
---	---	---	FIRE MAIN WATER LINE	EQUIPMENT			
--- S ---	--- S ---	--- S ---	SPRINKLER LINE	EXISTING	DEMO	NEW	DESCRIPTION
--- G ---	--- G ---	--- G ---	NATURAL GAS LINE	---	---	---	PLUMBING FIXTURES
---LP---	---LP---	---LP---	PROPANE GAS LINE	---	---	---	METER
---CA---	---CA---	---CA---	COMPRESSED AIR LINE	---	---	---	REGULATOR
---RO---	---RO---	---RO---	REVERSE OSMOSIS PURE WATER SUPPLY LINE	SYMBOL (MISC.)			
---ROR---	---ROR---	---ROR---	REVERSE OSMOSIS PURE WATER RETURN LINE	EXISTING	DEMO	NEW	DESCRIPTION
---DI---	---DI---	---DI---	DIONIZED PURE WATER SUPPLY LINE	---	---	---	CONNECT TO EXISTING SERVICES
---O---	---O---	---O---	OXYGEN LINE (MEDICAL)				
---VAC---	---VAC---	---VAC---	VACUUM LINE (MEDICAL)				
---N---	---N---	---N---	NITROGEN LINE (MEDICAL)				
---NO---	---NO---	---NO---	NITROUS OXIDE (MEDICAL)				
---MA---	---MA---	---MA---	AIR (MEDICAL)				
---WAGD---	---WAGD---	---WAGD---	WASTE ANESTHETIC GAS DISPOSAL				
PIPE FITTING							
EXISTING	DEMO	NEW	DESCRIPTION				
---	---	---	CAPPED PIPE				
---	---	---	PIPE RISE				
---	---	---	PIPE DROP				
---	---	---	UNION				
---	---	---	DIRECTION OF FLOW				
---	---	---	PIPE SUPPORT OR BRACING				
---	---	---	PIPE CONNECTION (TOP)				
---	---	---	PIPE CONNECTION (BOTTOM)				
---	---	---	PIPE CONNECTION (SIDE)				
---	---	---	CAPPED OUTLET TOP				
---	---	---	PIPE REDUCER AND/OR INCREASER				

NOTES: 1. EXISTING ITEMS ON DEMO PLANS ARE "EXISTING TO REMAIN" UNLESS NOTED "EXISTING TO BE RELOCATED."
2. ITEMS ON NEW CONSTRUCTION PLANS ARE NEW UNLESS NOTED "RELOCATED FROM PREVIOUS LOCATION". REFER TO SCHEDULES AND SPECIFICATIONS FOR PLUMBING FIXTURES.
3. NOT ALL ITEMS SHOWN ON THIS LIST MAY BE APPLICABLE TO THIS PROJECT.


DELIVER

PLUMBING & SPRINKLER GENERAL NOTES

- CONTRACTOR SHALL VISIT THE SITE AND DETERMINE THE EXTENT OF DEMOLITION WORK AND NEW WORK NEEDED FOR THIS PROJECT, PRIOR TO SUBMITTING BID.
- CONTRACTOR SHALL BECOME FAMILIAR WITH THE PROJECT SCOPE, CONSTRAINTS, UTILITY CONNECTIONS, AND BUILDING SERVICES, PRIOR TO SUBMITTING BID.
- CONTRACTOR SHALL GIVE FIRST RIGHT TO REFUSAL OF SALVAGE TO THE OWNER, IF THE OWNER ELECTS TO NOT KEEP SALVAGE, CONTRACTOR SHALL REMOVE SALVAGE BY LAWFUL MEANS.
- DRAWINGS ARE SCHEMATIC AND DIAGRAMMATIC IN NATURE. DRAWINGS SHALL NOT BE SCALED. COORDINATE ROUTING OF SERVICES WITH SITE CONDITIONS AND WITH WORK OF OTHER TRADES.
- FIELD VERIFY DIMENSIONS PRIOR TO ORDERING, FABRICATING, AND ERECTION OF MATERIAL AND/OR EQUIPMENT. NOTIFY THE ENGINEER OF DISCREPANCIES IN A TIMELY MANNER.
- VERIFY CLEARANCE REQUIREMENTS AND ROUTING OF PIPING PRIOR TO FABRICATION. AS MINOR MODIFICATIONS SUCH AS PIPING RISES AND DROP MAY BE REQUIRED DUE TO FIELD CONDITIONS, MAKE MINOR MODIFICATIONS TO THE BUILDING, PIPING, SPRINKLER, DUCTWORK, ELECTRICAL, ETC. AS SHOWN ON THE DRAWINGS OR REQUIRED TO COMPLETE THE INSTALLATION OF A COMPLETED WORKABLE SYSTEM.
- MAINTAIN WEATHER-TIGHT BARRIERS TO PREVENT DAMAGE FROM THE ELEMENTS DURING DEMOLITION AND NEW CONSTRUCTION PERIOD.
- SEAL PENETRATIONS THROUGH THE BUILDING ENVELOPE.
- PENETRATIONS THROUGH RATED WALLS, FLOORS, PARTITIONS AND ASSEMBLIES SHALL BE INSTALLED AND FIRESAFED TO MEET UL, FIRE RESISTANCE LISTING AND NFPA REQUIREMENTS FOR THE PENETRATION.
- COORDINATE DEVICES REQUIRING ACCESS PANELS WITH THE ARCHITECT AND OTHER TRADES.
- MAINTAIN MINIMUM CLEARANCE 10'-0" BETWEEN OUTSIDE INTAKES AND EXHAUST OUTLETS AND PLUMBING VENTS.
- COORDINATE FINAL LOCATIONS AND ELEVATIONS WITH THE ARCHITECT PRIOR TO INSTALLATION.
- COORDINATE FINAL FINISH COLORS OF MATERIALS, DEVICES, AND/OR EQUIPMENT WITH THE ARCHITECT PRIOR TO ORDERING, FABRICATION AND INSTALLATION.
- SCHEDULE UTILITY SERVICES SHUTDOWNS WITH OWNER AND ARCHITECT. MINIMIZE DISRUPTIONS AND DOWNTIME TO THE OWNER.
- INSTALL DEVICES AND EQUIPMENT TO MEET ADA REQUIREMENTS.
- ROUTE PIPING CONCEALED IN INTERSTITIAL SPACE UNLESS NOTED OTHERWISE.
- DOCUMENT LOCATIONS OF DEVICES, PIPING, AND EQUIPMENT ON "AS-BUILT" RECORD DRAWINGS AS PER THE SPECIFICATIONS.
- WORK SHOWN IN THE DRAWINGS SHALL COMPLY WITH APPLICABLE NATIONAL, STATE, AND LOCAL ORDINANCES AND CODES.
- ALL EXPOSED DOMESTIC COLD AND HOT WATER PIPING WITHIN THE BUILDING SHALL HAVE FIELD INSTALL PVC JACKET.
- WATER HAMMER ARRESTER(S) SHALL BE INSTALLED ON PIPING SYSTEMS AND AT QUICK-CLOSING VALVES AS PER MANUFACTURER'S RECOMMENDATIONS.


meconsulting.com

1304 BERTRAND DRIVE SUITE F7
LAFAYETTE, LOUISIANA 70506
(337) 234-7474 * FAX (337) 234-7774
Mechanical Contact: Dustin Duval
dustin@meconsulting.com
Electrical Contact: David Carroll
david@meconsulting.com
PROJECT No.: 21187.00




PLUMBING KEYNOTES:


- 1 ARGON GAS PRESSURE REGULATR WITH MANIFOLD SYSTEM FOR CYLINDER BOTTLES AND HEADER SYSTEM.
- 2 C25 GAS PRESSURE REGULATR WITH MANIFOLD SYSTEM FOR CYLINDER BOTTLES AND HEADER SYSTEM.
- 3 ARGON/C25 REGULATOR/FLOW METER AND QUICK DISCONNECT INERT GAS REGULATOR TO HOSE CONNECTION FOR ARGON AND C25 INERT GAS. INSTALL BALL TYPE SHUT-OFF VALVE UPSTREAM OF REGULATOR/FLOW METER. SHUT-OFF VALVE ON LINE NOT BEING USED SHALL BE CLOSED (TYPICAL). REFER TO DETAILS FOR ADDITIONAL INFORMATION.



2 WELDING GAS OUTLET DETAIL (ARGON & C25)
NO SCALE





3 WELDING PIPING SUPPORT DETAIL
NO SCALE



1 Plumbing Plan
1/8" = 1'-0" Refer to Architectural Drawings for All Dimensions

SAVED: P:\0000\1304 BERTRAND DRIVE SUITE F7\PROJECTS\1304 BERTRAND DRIVE SUITE F7\1304 BERTRAND DRIVE SUITE F7.dwg
 PLOTTED: 12/14/2021 10:01 AM
 PLOTTER: HP DesignJet T1100e
 PLOT SIZE: ARCH - expanded D (36.00 x 24.00 inches)
 (review)



SILSBEE HIGH SCHOOL WELDING SHOP FINISH-OUT
 Silsbee, TX 77656
 Silsbee Independent School District

ISSUED FOR SCHEMATIC DESIGN	<input type="checkbox"/>
DATE:	
DESIGN DEVELOPMENT	<input type="checkbox"/>
DATE:	
BIDS & CONSTRUCTION	<input checked="" type="checkbox"/>
DATE:	3/9/2022
REVISION:	
DATE:	
REVISION:	
DATE:	
REVISION:	
DATE:	

DRAWINGS SHEET TITLE
PLUMBING PLAN & DETAILS
 SHEET NUMBER
P201
 21051
 PROJECT NUMBER

1304 BERTRAND DRIVE SUITE F7
 LAFAYETTE, LOUISIANA 70506
 (337) 234-7474 • FAX (337) 234-7774
 Mechanical Contact: Dustin Duval
 dustin@meconsulting.com
 Electrical Contact: David Carroll
 david@meconsulting.com
 PROJECT No.: 21187.00